



## OML50 CT - 48V 100W 1,5m + PRISMATIC LENS D HO 1968mm 940 DIM5

31155 9405 B

BESCHIKBAAR IN  
ZWART 31155 9405 B

 [Bekijk op website](#)



### Algemene info

<b>LOCATIE</b>	binnen
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	3,6
<b>INFO</b>	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

### Elektrische info

<b>ELEKTRISCH</b>	220-240V / 0 50-60Hz
<b>KLASSE</b>	I
<b>VOEDING INBEGREPEN</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGIE KLASSE</b>	D
<b>CERTIFICATES</b>	EPD, RCM

### Info lichtbron

<b>LIGHTSOURCE NAME</b>	LED
<b>LICHTBRON</b>	LED cluster 46,5W / CRI>90 (R9: 50) / 4000K / 7274lm
<b>TM-30 WAARDEN</b>	Rf: 90 / Rg: 101
<b>SMDC</b>	SDCM3
<b>RISK-GROEP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNIEK (LICHTBRON)</b>	7274lm // 46,5W // 160lm/W

### Opties

WIRELESS CONTROL DIM5

Notes: