



LOGIC LINEAR ON 880 HONEYCOMB 94025 DIM5

30836 9425 W

AVAILABLE IN


ALU GREY 30836 9425 A

BLACK 30836 9425 B

FLEMISH BRONZE OUTDOOR 30836 9425 FBRX

ANTHRACITE 30836 9425 N

WHITE 30836 9425 W



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2
INFORMATION	16 x LENS FL-25° INCL.HONEYCOMB EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 64) / 4000K / 3898lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	25°
LED TECHNICS (LIGHT SOURCE)	3898lm // 28,8W // 131lm/W
LED TECHNICS (LUMINAIRE)	2271lm // 33,1W // 69lm/W

Requirements

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual : [30836_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
171 38 63	21032 0390 LED POWER SUPPLY 48V-DC / 90W Dimtype: non-dimmable Cutout dimension (mm): 75	2
Fixation components		
35 35 60	30810 0040 LOGIC LINEAR 880 BOX EXTEND	
	30810 0040 INOX WALL BRACKET SET 60 INOX	
	30810 0040 N WALL BRACKET SET 60 N	
28 45 100	30810 0050 INOX WALL BRACKET SET 100 INOX	
	30810 0050 N WALL BRACKET SET 100 N	
28 45 200	30810 0060 INOX WALL BRACKET SET 200 INOX	
	30810 0060 N WALL BRACKET SET 200 N	

DELTALIGHT

LOGIC LINEAR ON 880 HONEYCOMB 94025 DIM5

30836 9425 W



30810 0070 INOX FLOOR BRACKET SET INOX

☐

Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m

☐

30810 0090 IP68 CABLE + CONNECTOR 5P - 2m

☐

30810 0110 THROUGH WIRING SET IP68 880

☐

Notes: