



SPY 39 ON 2 92740 DIM8

24130 9238 BRC-B

AVAILABLE IN

NOIR-NOIR 24130 9238 B-B

ALU BROSSÉ-NOIR 24130 9238 BRA-B

ANTHRACITE BROSSÉ-NOIR 24130 9238 BRAT-B



CUIVRE BROSSÉ-NOIR 24130 9238 BRCU-B

OR BROSSÉ-NOIR 24130 9238 BRC-B

BRONZE VIEUX BROSSÉ-NOIR 24130 9238 BROB-B

ENTIÈREMENT BLANC 24130 9238 FW

BLANC-BLANC 24130 9238 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	0° à 85° inclinable, 355° rotatif
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm)
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	2082lm // 17,2W // 121lm/W
LED TECHNICS (LUMINAIRE)	1688lm // 19,8W // 85lm/W

Requirements

SPY 39 TUBE or VISOR 39

For detailed installation instructions, please consult the manual : [24130_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

modifier les dispositifs de lumière



24144 0030 B VISOR 39 B

☐

Terminez votre produit



24144 0010 B SPY 39 TUBE B

☐

24144 0010 FBR SPY 39 TUBE FBR

☐

24144 0010 FG SPY 39 TUBE FG

☐

24144 0010 GC SPY 39 TUBE GC

☐

24144 0010 W SPY 39 TUBE W

☐

24144 0070 SPY 39 TUBE SBL

☐

Notes: