
DELTALIGHT




# M - DOT.COM M4 92714 DIM5

**REFERENCE** 23355 9215 B-C

AVAILABLE IN
**BLACK-BLACK** 23355 9215 B-B
**BLACK-CHROMED** 23355 9215 B-C
**BLACK-FLEMISH GOLD** 23355 9215 B-FG



View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.2 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | 4 x REFLECTOR SP-14°<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 5,7W / CRI>90 (R9: 50) / 2700K / 631lm |
| **TM-30 VALUES** | Rf: 92 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 60000 |
| **BEAMANGLE** | 14° |
| **LED TECHNICS (LIGHT SOURCE)** | 631lm // 5,7W // 111lm/W |
| **LED TECHNICS (LUMINAIRE)** | 461lm // 6,6W // 70lm/W |

**Remarks**

**Take a look at our MAGNETIC PROFILES movie**

**Requirements**

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **23355_XXX5_HAND.pdf**

# M - DOT.COM M4 92714 DIM5

23355 9215 B-C


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**300 89 48 90** LED POWER SUPPLY 48V-DC / 90W — 12


**Dimtype: non-dimmable**

**Cutout dimension (mm): 75**





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 15

**Dimtype: non-dimmable**





**300 89 48 150** LED POWER SUPPLY 48V-DC / 150W — 21

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 37


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 15

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**




**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 31


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

## COMPATIBLE COMPOSABLES

### SHIFTLINE M26 profile


### Available Colours





**420 26 10 00** SLM26 - PROFILE 1m

# M - DOT.COM M4 92714 DIM5

23355 9215 B-C




**420 26 20 00** SLM26 - PROFILE 2m




**420 26 30 00** SLM26 - PROFILE 3m

## SHIFTLINE M26H + SBL


Available Colours





**30411 9205** SHIFTLINE M26H + SBL 2m DIM5





**30411 9305** SHIFTLINE M26H + SBL 2m DIM5





**30412 9205** SHIFTLINE M26H + SBL 3m DIM5




**30412 9305** SHIFTLINE M26H + SBL 3m DIM5





**30413 9205** SHIFTLINE M26H + SBL 4m DIM5




**30413 9305** SHIFTLINE M26H + SBL 4m DIM5

## SHIFTLINE M26H profile


Available Colours





**23359 0000** SLM26H - PROFILE

# M - DOT.COM M4 92714 DIM5


23355 9215 B-C




**23359 0010** SLM26H - PROFILE 1m





**23359 0020** SLM26H - PROFILE 2m





**23359 0030** SLM26H - PROFILE 3m


## SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX) — Available Colours





**23358 0000** SLM26L - PROFILE




**23358 0010** SLM26L - PROFILE 1m





**23358 0020** SLM26L - PROFILE 2m





**23358 0030** SLM26L - PROFILE 3m

## SHIFTLINE M35R profile — Available Colours





**23375 0000** SLM35R - PROFILE





**23375 0010** SLM35R - PROFILE 1m

# M - DOT.COM M4 92714 DIM5

23355 9215 B-C





**23375 0020** SLM35R - PROFILE 2m





**23375 0030** SLM35R - PROFILE 3m

## SHIFTLINE M44 profile


Available Colours




**23374 0000** SLM44 - PROFILE




**23374 0020** SLM44 - PROFILE 2m




**23374 0030** SLM44 - PROFILE 3m

## SPLITLINE M20 ST profile

Available Colours




**23397 0000** SPM20 ST - PROFILE





**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m

## SPLITLINE M20 profile

Available Colours





**420 20 10 00** SPM20 - PROFILE 1m


DELTALIGHT

# M - DOT.COM M4 92714 DIM5


23355 9215 B-C




**420 20 20 00** SPM20 - PROFILE 2m




**420 20 30 00** SPM20 - PROFILE 3m




**23301 0000** SPM20 - PROFILE B

Notes: