





D-LINER 19 SBL LOC2 1020 940 RD

32047 9400 B

AVAILABLE IN
BLACK 32047 9400 B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 650mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male green
Electrical info	
CLASS	III
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 25W / CRI>90 (R9: 59) / 4000K / 2600lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	2600lm // 25W // 1m/W
LED TECHNICS (LUMINAIRE)	1950lm // 28,8W // 68lm/W
Requirements	
LED POWER SUPPLY SET LOC PARALLEL	
Options	
CONNECTING CABLE LOC PARALLEL	

For detailed installation instructions, please consult the manual : [32047_XXX0_HAND.pdf](#)

DELTALIGHT

D-LINER 19 SBL LOC2 1020 940 RD

32047 9400 B

CEILING COMPATIBILITY

Ceiling Type

Mounting Kit



Acoustic climate-control ceiling Interalu WEC


FINISH YOUR SPECIFICATION

Emergency units

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5

Dimtype: DALI

1

Current supply



32010 1200 T CONNECTOR LOC PARALLEL



32010 1310 CONNECTING CABLE LOC PARALLEL 1m



32010 1320 CONNECTING CABLE LOC PARALLEL 2m



32010 1330 CONNECTING CABLE LOC PARALLEL 3m



32010 1340 CONNECTING CABLE LOC PARALLEL 4m

DELTALIGHT

D-LINER 19 SBL LOC2 1020 940 RD

32047 9400 B



32010 1350 CONNECTING CABLE LOC PARALLEL 5m


☐

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



32010 0115 LED POWER SUPPLY SET LOC PARALLEL 650mA / 35W DIM5

1 ☐


Dimtype: DALI



32010 0165 LED POWER SUPPLY SET LOC PARALLEL 1300mA /100W DIM5

2->2 ☐

Dimtype: DALI



32010 0445 LED POWER SUPPLY SET LOC PARALLEL 1950mA /100W DIM5

3->3 ☐

Dimtype: DALI

Notes: