





M20/M26H - OCTAV 39 92740
DIM5

29022 9235 GC

AVAILABLE IN
BLACK 29022 9235 B
FLEMISH BRONZE 29022 9235 FBR
FLEMISH GOLD 29022 9235 FG
GOLD COLOURED 29022 9235 GC
WHITE 29022 9235 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° EXCLLED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	705lm // 9,9W // 71lm/W
Remarks	
Take a look at our MAGNETIC PROFILES movie	
Requirements	
SPY 39 L TUBE LED POWER SUPPLY 48V-DC	

For detailed installation instructions, please consult the manual : [29022_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

Finish your product



24144 0020 B SPY 39 L TUBE B

24144 0020 FBR SPY 39 L TUBE FBR

24144 0020 FG SPY 39 L TUBE FG

24144 0020 GC SPY 39 L TUBE GC



24144 0020 W SPY 39 L TUBE W




DELTALIGHT

M20/M26H - OCTAV 39 92740 DIM5

29022 9235 GC

COMPATIBLE COMPOSABLES


SHIFTLINE M26H + SBL		Available Colours
	30411 9205 SHIFTLINE M26H + SBL 2m DIM5	
	30411 9305 SHIFTLINE M26H + SBL 2m DIM5	
	30412 9205 SHIFTLINE M26H + SBL 3m DIM5	
	30412 9305 SHIFTLINE M26H + SBL 3m DIM5	
	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	

SHIFTLINE M26H profile		Available Colours
	23359 0000 SLM26H - PROFILE	
	23359 0010 SLM26H - PROFILE 1m	
	23359 0020 SLM26H - PROFILE 2m	

DELTALIGHT

M20/M26H - OCTAV 39 92740 DIM5

29022 9235 GC



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: