



**OML50 CT - 48V 200W 2,0m +  
PRISMATIC LENS D HO 2296mm  
930 DIM5**  
31156 9305 B

AVAILABLE IN  
**BLACK** 31156 9305 B

 [View on website](#)



General info

|                    |                                                                          |
|--------------------|--------------------------------------------------------------------------|
| LOCATION           | indoor                                                                   |
| INGRESS PROTECTION | IP20                                                                     |
| WEIGHT (KG)        | 3.7                                                                      |
| INFORMATION        | INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |

Electrical info

|              |                      |
|--------------|----------------------|
| ELECTRICAL   | 220-240V / 0 50-60Hz |
| CLASS        | I                    |
| POWER SUPPLY | YES                  |
| DIM TYPE     | DALI                 |
| ENERGY CLASS | D                    |
| CERTIFICATES | EPD, RCM             |

Lightsource info

|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                                  |
| LIGHTSOURCE                 | LED cluster 54,3W / CRI>90 (R9: 50) / 3000K / 8330lm |
| TM-30 VALUES                | Rf: 92 / Rg: 100                                     |
| SDCM                        | SDCM3                                                |
| RISKGROUP                   | RG1                                                  |
| LM80                        | L80 > 60000                                          |
| LED TECHNICS (LIGHT SOURCE) | 8330lm // 54,3W // 153lm/W                           |

Options

WIRELESS CONTROL DIM5

Notes: