



## M26L - SPY 52 SOFT 93020 DIM5

23298 9025 B

AVAILABLE IN



**BLACK** 23298 9025 B

**FLEMISH BRONZE** 23298 9025 FBR

**FLEMISH GOLD** 23298 9025 FG

**GOLD COLOURED** 23298 9025 GC

**WHITE** 23298 9025 W



[View on website](#)



### General info

|                           |                                                                                            |
|---------------------------|--------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                     |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                                             |
| <b>INGRESS PROTECTION</b> | IP20                                                                                       |
| <b>WEIGHT (KG)</b>        | 0.4                                                                                        |
| <b>ADJUSTABILITY</b>      | 0° to 90° swiveling, 360° rotatable                                                        |
| <b>INFORMATION</b>        | REFLECTOR FL-20°<br>EXCLLED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 30° & 45° available |

### Electrical info

|                     |               |
|---------------------|---------------|
| <b>ELECTRICAL</b>   | 48V-DC        |
| <b>CLASS</b>        | III           |
| <b>DIM TYPE</b>     | DALI          |
| <b>ENERGY CLASS</b> | F             |
| <b>CERTIFICATES</b> | CB, ENEC, EPD |

### Lightsource info

|                                    |                                                          |
|------------------------------------|----------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                      |
| <b>LIGHTSOURCE</b>                 | LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm |
| <b>SDCM</b>                        | SDCM2                                                    |
| <b>RISKGROUP</b>                   | RG1                                                      |
| <b>LM80</b>                        | L90B10 > 50000                                           |
| <b>BEAMANGLE</b>                   | 20°                                                      |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1038lm // 10,2W // 109lm/W                               |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 650lm // 11,7W // 55lm/W                                 |

### Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

### Requirements

SPY 52 TUBE

LED POWER SUPPLY 48V-DC

### Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42

SOFTENING LENS 42

GLASS SBL 42

# DELTALIGHT

## M26L - SPY 52 SOFT 93020 DIM5

23298 9025 B

For detailed installation instructions, please consult the manual : [23298\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

8


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

8

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

17


Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices



**19810 0010 B** HONEYCOMB 42 SINGLE USE B



**19810 0020** LINEAR SPREAD LENS 42

# DELTALIGHT

## M26L - SPY 52 SOFT 93020 DIM5

23298 9025 B



**19810 0030** SPREAD LENS 42

☐

**19810 0040** SOFTENING LENS 42

☐

**19810 0050** GLASS SBL 42

☐

**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

☐

### Finish your product



**19810 0100 B** SPY 52 TUBE B

☐

**19810 0100 FBR** SPY 52 TUBE FBR

☐

**19810 0100 FG** SPY 52 TUBE FG

☐

**19810 0100 GC** SPY 52 TUBE GC

☐

**19810 0100 W** SPY 52 TUBE W

☐

### Replaceable reflector / lens



**19810 0180** SPY 52 REFLECTOR 20°

☐

# DELTALIGHT

## M26L - SPY 52 SOFT 93020 DIM5

23298 9025 B



**19810 0190** SPY 52 REFLECTOR 45°




**19810 0240** SPY 52 REFLECTOR 30°




### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


#### Available Colours




**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m




**23358 0030** SLM26L - PROFILE 3m




#### SHIFTLINE M35R profile

#### Available Colours



**23375 0000** SLM35R - PROFILE




**23375 0010** SLM35R - PROFILE 1m




# DELTALIGHT

## M26L - SPY 52 SOFT 93020 DIM5

23298 9025 B



**23375 0020** SLM35R - PROFILE 2m



**23375 0030** SLM35R - PROFILE 3m



Notes: