DELTALIGHT



ENTERO SQ-S TRIMLESS IP TW 96520

REFERENCE 28552 9020 FW

AVAILABLE IN
BLACK 28552 9020 B
FULL WHITE 28552 9020 FW
GOLD COLOURED 28552 9020 GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	120
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.24
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	704lm // 10W // 68lm/W

Requirements

MOUNTING KIT ENTERO SQUARE S
LED POWER SUPPLY 500mA-DC TW (Remote)

For detailed installation instructions, please consult the manual : **28552_XXX0_HAND.pdf**

DELTALIGHT

ENTERO SQ-S TRIMLESS IP TW 96520

28552 9020 FW

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 **Plasterboard**	28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 **Stucanet**	28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 **Wood**	28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 **Concrete + plaster**	28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 **Lintel + plaster**	28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 **Hollow-core slab + plaster**	28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 **Stretched ceiling**	28400 0160 - MOUNTING KIT ENTERO SQ-S WSC	Required
	28400 0100 - MOUNTING KIT ENTERO SQ-S CSC	Required

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 85

Mounting kits



28400 0040 MOUNTING KIT ENTERO SQ-S

Cutout dimension (mm): 106 x 106

DELTALIGHT

ENTERO SQ-S TRIMLESS IP TW 96520

28552 9020 FW

Mounting kits stretched ceiling



28400 0100 MOUNTING KIT ENTERO SQ-S CSC ☐



28400 0160 MOUNTING KIT ENTERO SQ-S WSC ☐

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20° ☐



19810 0190 SPY 52 REFLECTOR 45° ☐



19810 0240 SPY 52 REFLECTOR 30° ☐

Notes: