



## SUPERLOOP-SPY 52 92720 MDL

20567 9220 FG

AVAILABLE IN



**BLACK** 20567 9220 B

**FLEMISH BRONZE** 20567 9220 FBR

**FLEMISH GOLD** 20567 9220 FG

**GOLD COLOURED** 20567 9220 GC

**WHITE** 20567 9220 W



[View on website](#)



### General info

|                           |                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                               |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                                                                       |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                 |
| <b>WEIGHT (KG)</b>        | 0.4                                                                                                                  |
| <b>ADJUSTABILITY</b>      | 0° to 90° swiveling, 355° rotatable                                                                                  |
| <b>INFORMATION</b>        | REFLECTOR FL-20°<br>INCL.CLIP 48V ADAPTER<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 30° & 45° available |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | E                                  |
| <b>CERTIFICATES</b> | CB, ENEC                           |

### Lightsource info

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                  |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>BEAMANGLE</b>                   | 20°                                               |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1041lm // 8,6W // 121lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 652lm // 9,9W // 66lm/W                           |

### Requirements

SPY 52 TUBE

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

### Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42

SOFTENING LENS 42

## SUPERLOOP-SPY 52 92720 MDL

20567 9220 FG

GLASS SBL 42

For detailed installation instructions, please consult the manual : [20567\\_XXX0\\_HAND.pdf](#)

## FINISH YOUR SPECIFICATION


### SMART 48

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

19

Dimtype: WDL = wireless dimmable


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40

# DELTALIGHT

## SUPERLOOP-SPY 52 92720 MDL

20567 9220 FG



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

Dimtype: non-dimmable

Cutout dimension (mm): 40


20 ☐

### Light altering devices




**19810 0010 B** HONEYCOMB 42 SINGLE USE B

☐



**19810 0020** LINEAR SPREAD LENS 42

☐




**19810 0030** SPREAD LENS 42

☐




**19810 0040** SOFTENING LENS 42

☐



**19810 0050** GLASS SBL 42


☐



**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

☐

### Finish your product



**19810 0100 B** SPY 52 TUBE B

☐

**19810 0100 FBR** SPY 52 TUBE FBR

☐

# DELTALIGHT

## SUPERLOOP-SPY 52 92720 MDL




20567 9220 FG

|                      |                |                          |
|----------------------|----------------|--------------------------|
| <b>19810 0100 FG</b> | SPY 52 TUBE FG | <input type="checkbox"/> |
| <b>19810 0100 GC</b> | SPY 52 TUBE GC | <input type="checkbox"/> |
| <b>19810 0100 W</b>  | SPY 52 TUBE W  | <input type="checkbox"/> |

### Replaceable reflector / lens

|                                                                                    |                                        |                          |
|------------------------------------------------------------------------------------|----------------------------------------|--------------------------|
|    | <b>19810 0180</b> SPY 52 REFLECTOR 20° | <input type="checkbox"/> |
|   | <b>19810 0190</b> SPY 52 REFLECTOR 45° | <input type="checkbox"/> |
|  | <b>19810 0240</b> SPY 52 REFLECTOR 30° | <input type="checkbox"/> |


## COMPATIBLE COMPOSABLES

| SUPERLOOP HC MDL                                                                                                          | Available Colours                                                                                                                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <b>418 481 07</b> SUPERLOOP HC 70 MDL  |    |
|  <b>418 481 09</b> SUPERLOOP HC 90 MDL  |    |
|  <b>418 481 12</b> SUPERLOOP HC 120 MDL |    |

# DELTALIGHT

## SUPERLOOP-SPY 52 92720 MDL

20567 9220 FG




**418 481 17**

SUPERLOOP HC 170 MDL



### SUPERLOOP HC MDL XL


Available Colours



**20555 0000**

SUPERLOOP HC 200 MDL






**20556 0000**

SUPERLOOP HC 250 MDL






**20557 0000**

SUPERLOOP HC 300 MDL






**20558 0000**

SUPERLOOP HC 350 MDL






**20559 0000**

SUPERLOOP HC 400 MDL






**20560 0000**

SUPERLOOP HC 500 MDL



### SUPERLOOP PLUS MDL


Available Colours



**20564 0000**

SUPERLOOP PLUS HC 70 MDL





**20565 0000**


SUPERLOOP PLUS HC 90 MDL



# DELTALIGHT

## SUPERLOOP-SPY 52 92720 MDL

20567 9220 FG




20566 0000

SUPERLOOP PLUS HC 120 MDL



### SUPERLOOP S HC MDL


Available Colours



418 482 106

SUPERLOOP S HC 106 MDL






418 482 109

SUPERLOOP S HC 109 MDL






418 482 211

SUPERLOOP S HC 211 MDL





418 482 217

SUPERLOOP S HC 217 MDL



Notes: