



## SL19 - SPY 39 92740 MDL

27024 9230 W

AVAILABLE IN



**BLACK** 27024 9230 B

**FLEMISH BRONZE** 27024 9230 FBR

**FLEMISH GOLD** 27024 9230 FG

**GOLD COLOURED** 27024 9230 GC

**WHITE** 27024 9230 W



[View on website](#)



### General info

|                           |                                                  |
|---------------------------|--------------------------------------------------|
| <b>LOCATION</b>           | indoor                                           |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted   |
| <b>INGRESS PROTECTION</b> | IP20                                             |
| <b>WEIGHT (KG)</b>        | 0.3                                              |
| <b>ADJUSTABILITY</b>      | 0° to 85° swiveling, 355° rotatable              |
| <b>INFORMATION</b>        | REFLECTOR WFL-40°<br>EXCLLED POWER SUPPLY 48V-DC |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | E                                  |
| <b>CERTIFICATES</b> | CB, ENEC                           |

### Lightsource info

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                  |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>BEAMANGLE</b>                   | 40°                                               |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1041lm // 8,6W // 121lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 844lm // 9,9W // 85lm/W                           |

### Requirements

SPY 39 TUBE or VISOR 39  
LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [27024\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### SMART 48

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

19

Dimtype: WDL = wireless dimmable


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable


Cutout dimension (mm): 40

# DELTALIGHT

## SL19 - SPY 39 92740 MDL

27024 9230 W


### Light altering devices



**24144 0030 B** VISOR 39 B

☐

### Finish your product



**24144 0010 B** SPY 39 TUBE B

☐

**24144 0010 FBR** SPY 39 TUBE FBR

☐

**24144 0010 FG** SPY 39 TUBE FG

☐

**24144 0010 GC** SPY 39 TUBE GC

☐

**24144 0010 W** SPY 39 TUBE W

☐


**24144 0070** SPY 39 TUBE SBL

☐


## COMPATIBLE COMPOSABLES

### SHIFTLINE 19 profile

### Available Colours



**27011 0050** SL19 - PROFILE 2m



**27011 0060** SL19 - PROFILE 3m



# DELTALIGHT

## SL19 - SPY 39 92740 MDL

27024 9230 W

Notes: