

24174 9300 FBR

NOIR 24174 9300 B

ALU BROSSÉ 24174 9300 BRA

ANTHRACITE BROSSÉ 24174 9300 BRAT

CUIVRE BROSSÉ 24174 9300 BRCU

OR BROSSÉ 24174 9300 BRG

BRONZE VIEUX BROSSÉ 24174 9300 BROB



FLEMISH BRONZE 24174 9300 FBR

FLEMISH GOLD 24174 9300 FG

ENTIÈREMENT BLANC 24174 9300 FW

COULEUR OR 24174 9300 GC

BLANC 24174 9300 W



[View on website](#)










Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROU	RG1
LM80	L90B10 > 50000
BEAMANGLE	15°-45°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	303lm // 9,9W // 31lm/W

LED POWER SUPPLY 350 / 500mA-DC DIM

COVERSET R 90-100






For detailed installation instructions, please consult the manual : [24174_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

les alimentations led			# of Fixtures
 web2print_power_supply_info_box			Min current Max current
	300 48 350 ED1	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1	2 ☐
	Dimtype: 1 à 10 V		
	Cutout dimension (mm): 30		
	300 48 350 ED5	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	2 ☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 350 MDL	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	2 ☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 30		
	300 48 350 WDL	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	2 ☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 45		
	300 48 500 ED1	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	2 ☐
	Dimtype: 1 à 10 V		
	Cutout dimension (mm): 30		
	300 48 500 ED5	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2 ☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 500 MDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	2 ☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 30		

SPY 39 ON FOCUS 930




24174 9300 FBR

	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45	2	☐
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: fin de phase ou bouton poussoir Cutout dimension (mm): 56	2 2	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 82	4(4) 4(4)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 72	2(2) 2(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir	2 -	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	2(2) 2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 84	2->6(6) 6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55	2(2) 2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) 2(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	3->4 2->4	☐

DELTALIGHT

SPY 39 ON FOCUS 930





24174 9300 FBR

	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	2 2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	3 3	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	3 3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	4(4) 3(3)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	3 3	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	2->2 2->2	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	2->3	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	2 2	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐

DELTALIGHT

SPY 39 ON FOCUS 930

24174 9300 FBR

	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(2)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐

les sets pour recouvrement plafond

	204 00 100 ANO COVERSET R 100 ANO	☐
	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐

Notes: