



LUNELLE 52 TRIMLESS 93030

32811 9320 BRA

AVAILABLE IN

BRUSHED ALU 32811 9320 BRA



BRUSHED ANTHRACITE 32811 9320 BRAT

BRUSHED BROWN BRONZE 32811 9320 BRBB

BRUSHED COPPER 32811 9320 BRCU

BRUSHED GOLD 32811 9320 BRG

BRUSHED OLD BRONZE 32811 9320 BROB



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø kit
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 / 3000K / 519lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	519lm // 5,6W // 92lm/W
LED TECHNICS (LUMINAIRE)	415lm // 6,4W // 64lm/W

Requirements

MOUNTING KIT R53 TRIMLESS
LED POWER SUPPLY 500mA-DC

Accessories

VISOR 52









For detailed installation instructions, please consult the manual : [32811_XXX0_HAND.pdf](#)

DELTALIGHT

LUNELLE 52 TRIMLESS 93030

32811 9320 BRA

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 Plasterboard	 32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required
 Concrete + plaster	 32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required
 Lintel + plaster	 32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

1 -> 6 (6)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1 -> 4 (2)

Dimtype: DALI

Cutout dimension (mm): 72




300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

1 -> 10 (7)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

1 -> 3 (2)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

1 -> 3 (2)


Dimtype: DALI

Cutout dimension (mm): 55

DELTALIGHT

LUNELLE 52 TRIMLESS 93030

32811 9320 BRA




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1 -> 4

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1 -> 3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0595 LED POWER SUPPLY 500mA-DC 10W DIM5

1 -> 1

Dimtype: DALI

Cutout dimension (mm): 35

Mounting kits



32210 0050 MOUNTING KIT R53 TRIMLESS O.F.A.

Cutout dimension (mm): 82

Light altering devices



32810 0010 DC VISOR 52 DC

Notes: