



## OML50 CT - 48V 200W 2,5m + PRISMATIC LENS D HO 2624mm 930 DIM5

31157 9305 B

BESCHIKBAAR IN  
ZWART 31157 9305 B



[Bekijk op website](#)



### Algemene info

|                        |                                                                          |
|------------------------|--------------------------------------------------------------------------|
| LOCATIE                | binnen                                                                   |
| STOF EN WATERDICHTHEID | IP20                                                                     |
| GEWICHT (KG)           | 4.1                                                                      |
| INFO                   | INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |

### Elektrische info

|                 |                      |
|-----------------|----------------------|
| INGANGSSPANNING | 220-240V / 0 50-60Hz |
| KLASSE          | I                    |
| VOEDING         | YES                  |
| DIM TYPE        | DALI                 |
| ENERGIE KLASSE  | D                    |
| CERTIFICATEN    | EPD, RCM             |

### Info lichtbron

|                          |                                                    |
|--------------------------|----------------------------------------------------|
| LIGHTSOURCE NAME         | LED                                                |
| LICHTBRON                | LED cluster 62W / CRI>90 (R9: 50) / 3000K / 9520lm |
| TM-30-15 WAARDEN         | Rf: 92 / Rg: 100                                   |
| SDCM                     | SDCM3                                              |
| RISK-GROEP               | RG1                                                |
| LM80                     | L80 > 60000                                        |
| LED TECHNIEK (LICHTBRON) | 9520lm // 62W // 153lm/W                           |

### Opties

WIRELESS CONTROL DIM5

Notes: