

## DEEP RINGO DYNAMIC FOCUS 927

32111 9200 B

AVAILABLE IN

**BLACK** 32111 9200 B

**BRUSHED ALU** 32111 9200 BRA

**BRUSHED ANTHRACITE** 32111 9200 BRAT

**BRUSHED BROWN BRONZE** 32111 9200 BRBB

**BRUSHED COPPER** 32111 9200 BRCU


**BRUSHED GOLD** 32111 9200 BRG

**BRUSHED OLD BRONZE** 32111 9200 BROB

**CREAM** 32111 9200 CR

**PIANO BLACK** 32111 9200 PB

**WHITE** 32111 9200 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 76
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	xxxx
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	non adjustable

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	G

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	13° (central part only): LED array 5,8W / CRI>90 (R9: 56) / 2700K / 528lm Or 24° central part: LED array 1W / CRI>90 (R9: 56) / 2700K / 63lm 24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 2700K / 868lm
<b>TM-30 VALUES</b>	13° (central part only): rf: 91 / Rg: 99 24° central part: rf: 91 / Rg: 99 24° ring part: rf: 93 / Rg: 100
<b>SDCM</b>	SDCM2 SDCM3
<b>RISKGROUP</b>	RG2 (threshold 0,6m) RG1
<b>LM80</b>	L90B10 > 41000 L80 > 60000
<b>BEAMANGLE</b>	13°-24°
<b>LED TECHNICS (LIGHT SOURCE)</b>	13° (central part only): 528lm // 5,8W // 94lm/W Or 24° central part: 63lm // 1W // 100lm/W 24° ring part: 868lm // 5,5W // 158lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	13° (central part only): 475lm // 6,7W // 71lm/W Or 24° ring part: 347lm // 6,3W // 55lm/W

# DELTALIGHT

## DEEP RINGO DYNAMIC FOCUS 927

32111 9200 B

### Requirements

LED POWER SUPPLY DYNAMIC FOCUS

For detailed installation instructions, please consult the manual : [32111\\_XXX0\\_HAND.pdf](#)

## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**32110 0015** LED POWER SUPPLY DYNAMIC FOCUS DIM5

3

Dimtype: DALI

Cutout dimension (mm): 75



**32110 0020** LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5

3

Dimtype: DALI

Cutout dimension (mm): 75

Notes: