





iMAX II ROUND ADJUSTABLE MP
92718

24211 9210 B

AVAILABLE IN
BLACK 24211 9210 B
WHITE 24211 9210 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 98
RECESSED DEPTH (MM)	155
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20 or IP54 (with TUBE IP)
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	LENS SP-18° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-17,2W / CRI>90 (R9: 60) / 2700K / 1458-2009lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	2009lm // 17,2W // 117lm/W
LED TECHNICS (LUMINAIRE)	1387lm // 19,8W // 70lm/W

Requirements	
iMAX II TUBE ROUND	
LED POWER SUPPLY 350 / 500mA-DC DIM	

Accessories	
iMAX II ACCESSOIRES	

For detailed installation instructions, please consult the manual : [24211_XXXX_HAND.pdf](#)

iMAX II ROUND ADJUSTABLE MP 92718


24211 9210 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	 15215 0010 - MOUNTING KIT FLUSH iMAX II ROUND Required
 Plasterboard	 15215 0010 - MOUNTING KIT FLUSH iMAX II ROUND Required
 Stucanet	 15215 0010 - MOUNTING KIT FLUSH iMAX II ROUND Required
 Wood	-
 Stretched ceiling	-



FINISH YOUR SPECIFICATION

Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B ☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W ☐











LED power supplies

of Fixtures

	# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1-10V Cutout dimension (mm): 30	1 ☐
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	1 ☐











iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 B

	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL Dimtype: non-dimmable Cutout dimension (mm): 30	1	☐
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 45	1	☐
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 Dimtype: 1-10V Cutout dimension (mm): 30	1	☐
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 45	1	☐
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL Dimtype: non-dimmable Cutout dimension (mm): 30	1	☐
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 45	1	☐
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: mains (phase cut-off) or push button Cutout dimension (mm): 56	1 1	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	2(2) 2(2)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1(1) 1(0)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	1 -	☐








iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 B

	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1(1) 1(0)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	3(3) 3(2)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	1(1) 1(0)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1) 1(0)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	2->2 2	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	1 1	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1 1	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1 1	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	2(2) 2(2)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	1 1	☐

iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 B

	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	1	☐
	Dimtype: mains (phase cut-off)		
	Cutout dimension (mm): 50		
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	1	☐
	Dimtype: mains (phase cut-off)		
	Cutout dimension (mm): 55		
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1 1	☐
	Dimtype: mains (phase cut-off)		
	Cutout dimension (mm): 48		
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1 (1)	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 60		
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1 (0)	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 60		
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		

Mounting kits


	15215 0010 MOUNTING KIT FLUSH iMAX II ROUND		☐
	Cutout dimension (mm): 121		

DELTALIGHT


iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 B


Light altering devices



24213 0050 B iMAX II HONEYCOMB B

☐

24213 0060 iMAX II GLASS SBL

☐

24213 0070 iMAX II LINEAR SPREAD LENS

☐


24213 0090 iMAX II SOFTENING LENS

☐

24213 0100 iMAX II SPREAD LENS

☐

Finish your product



24213 0010 B iMAX II TUBE ROUND B

☐


24213 0010 FG iMAX II TUBE ROUND FG

☐

24213 0010 MMAT iMAX II TUBE ROUND MMAT

☐

24213 0010 W iMAX II TUBE ROUND W

☐

24213 0040 B iMAX II TUBE ROUND IP B

☐

DELTALIGHT

iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 B

<u>24213 0040 FG</u>	iMAX II TUBE ROUND IP FG	☐
<u>24213 0040 MMAT</u>	iMAX II TUBE ROUND IP MMAT	☐
<u>24213 0040 W</u>	iMAX II TUBE ROUND IP W	☐

Notes: