

DEEP RINGO DYNAMIC FOCUS 930

32111 9300 B

AVAILABLE IN

BLACK 32111 9300 B

BRUSHED ALU 32111 9300 BRA

BRUSHED ANTHRACITE 32111 9300 BRAT

BRUSHED BROWN BRONZE 32111 9300 BRBB

BRUSHED COPPER 32111 9300 BRCU


BRUSHED GOLD 32111 9300 BRG

BRUSHED OLD BRONZE 32111 9300 BROB

CREAM 32111 9300 CR

PIANO BLACK 32111 9300 PB

WHITE 32111 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
THICKNESS OF MOUNTING SURFACE (MM)	xxxx
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	13° (central part only): LED array 5,8W / CRI>90 (R9: 55) / 3000K / 528lm Or 24° central part: LED array 1W / CRI>90 (R9: 55) / 3000K / 63lm 24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 3000K / 914lm
TM-30 VALUES	13° (central part only): rf: 92 / Rg: 98 24° central part: rf: 92 / Rg: 98 24° ring part: rf: 92 / Rg: 100
SDCM	SDCM2 SDCM3
RISKGROUP	RG2 (threshold 0,6m) RG1
LM80	L90B10 > 41000 L80 > 60000
BEAMANGLE	13°-24°
LED TECHNICS (LIGHT SOURCE)	13° (central part only): 528lm // 5,8W // 94lm/W Or 24° central part: 63lm // 1W // 100lm/W 24° ring part: 914lm // 5,5W // 167lm/W
LED TECHNICS (LUMINAIRE)	13° (central part only): 475lm // 6,7W // 71lm/W Or 24° ring part: 366lm // 6,3W // 58lm/W

DELTALIGHT

DEEP RINGO DYNAMIC FOCUS 930

32111 9300 B

Requirements

LED POWER SUPPLY DYNAMIC FOCUS

For detailed installation instructions, please consult the manual : [32111_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




32110 0015 LED POWER SUPPLY DYNAMIC FOCUS DIM5

3

Dimtype: DALI

Cutout dimension (mm): 75



32110 0020 LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5

3

Dimtype: DALI

Cutout dimension (mm): 75

Notes: