





M - HEDRA 39 C 92745 DIM5

22539 9235 B

AVAILABLE IN
BLACK 22539 9235 B
BLACK BRONZE 22539 9235 BBR
GOLD COLOURED 22539 9235 GC
WHITE 22539 9235 W



 [View on website](#)





General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC INCL.1 x CABLE 2 x 0.75mm ²
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	507lm // 6,7W // 76lm/W
Requirements	
LED POWER SUPPLY 48V-DC	
Options	
DIMMABLE MODULATOR	

For detailed installation instructions, please consult the manual : [22539_XXX5_HAND.pdf](#)

M - HEDRA 39 C 92745 DIM5

22539 9235 B

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable		12
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable		29
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40		12
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40		24



COMPATIBLE COMPOSABLES





SHIFTLINE M26H + SBL		Available Colours
 30411 9205 SHIFTLINE M26H + SBL 2m DIM5		
 30411 9305 SHIFTLINE M26H + SBL 2m DIM5		
 30412 9205 SHIFTLINE M26H + SBL 3m DIM5		



DELTALIGHT

M - HEDRA 39 C 92745 DIM5

22539 9235 B

	30412 9305 SHIFTLINE M26H + SBL 3m DIM5	 
	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	 
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	 


SHIFTLINE M26H profile	Available Colours
 23359 0000 SLM26H - PROFILE	 
 23359 0010 SLM26H - PROFILE 1m	 
 23359 0020 SLM26H - PROFILE 2m	         
 23359 0030 SLM26H - PROFILE 3m	         

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
 23358 0000 SLM26L - PROFILE	 
 23358 0010 SLM26L - PROFILE 1m	 


DELTALIGHT

M - HEDRA 39 C 92745 DIM5

22539 9235 B



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B







M - HEDRA 39 C 92745 DIM5

22539 9235 B

SPLITLINE M52 profile

Available Colours

	420 52 10 00 SPM52 - PROFILE 1m	
	420 52 20 00 SPM52 - PROFILE 2m	
	420 52 30 00 SPM52 - PROFILE 3m	
	24413 0000 SPM52 - PROFILE	

Notes: