




SPIX P70-2 93010

29717 9310 N

AVAILABLE IN
ANTHRACITE 29717 9310 N
PINE GREEN 29717 9310 PGR



 [View on website](#)




General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK05
WEIGHT (KG)	1.8
ADJUSTABILITY	90° swiveling, 360° rotatable
INFORMATION	LENS 10° INCLLED POWER SUPPLY 700mA-DC
Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 2W / CRI>90 (R9: 60) / 3000K / 240lm)
TM-30 VALUES	rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
BEAMANGLE	10°
LED TECHNICS (LIGHT SOURCE)	480lm // 4W // 120lm/W
LED TECHNICS (LUMINAIRE)	377lm // 4,6W // 82lm/W

Requirements
PIN 11
PLATE 12
Options
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : [29717_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

☐

Cutout dimension (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT

☐


216 12 02 IP68 CONNECTOR 3P

☐

Pins and plates for bollards



229 01 11 PIN 11

☐

15223 0120 N PLATE 12 N

☐

Notes: