



ENTERO SQ-L TW 96530



28520 9020 B

AVAILABLE IN

BLACK 28520 9020 B

FULL WHITE 28520 9020 FW

GOLD COLOURED 28520 9020 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 112 x 112
RECESSED DEPTH (MM)	160
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.68
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 18° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1661lm // 20,5W // 81lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

Accessories


ENTERO L HONEYCOMB
ENTERO L LINEAR SPREAD LENS
ENTERO L SPREAD LENS
ENTERO L SOFTENING LENS
ENTERO L GLASS SBL

For detailed installation instructions, please consult the manual : [28520_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the 'I' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 Dimtype: DALI Cutout dimension (mm): 85	1 ☐
Light altering devices		
	28500 0130 ENTERO L LINEAR SPREAD LENS	☐


DELTALIGHT

ENTERO SQ-L TW 96530


28520 9020 B




28500 0140 ENTERO L SPREAD LENS

☐


28500 0150 ENTERO L SOFTENING LENS

☐

28500 0160 ENTERO L GLASS SBL

☐

28500 0170 B ENTERO L HONEYCOMB SINGLE USE B

☐

28500 0180 B ENTERO L HONEYCOMB DOUBLE USE B

☐

Notes: