

## SPY 52 TRIMLESS HE 92740

19807 9230 W

AVAILABLE IN



**BLACK** 19807 9230 B

**FLEMISH BRONZE** 19807 9230 FBR

**FLEMISH GOLD** 19807 9230 FG

**GOLD COLOURED** 19807 9230 GC

**WHITE** 19807 9230 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - Ø KIT
<b>RECESSED DEPTH (MM)</b>	80
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.4
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 355° rotatable
<b>INFORMATION</b>	LENS WFL-40° EXCL.LED POWER SUPPLY 350mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	D

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm
<b>TM-30 VALUES</b>	rf: 96 / Rg: 99
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	40°
<b>LED TECHNICS (LIGHT SOURCE)</b>	905lm // 6W // 150lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	704lm // 6,9W // 102lm/W

### Remarks

High Efficacy : > 100lm/W

### Requirements

SPY 52 TUBE

MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.

MOUNTING KIT AIR 103

LED POWER SUPPLY 350mA-DC DIM (Remote)



# DELTALIGHT

## SPY 52 TRIMLESS HE 92740

19807 9230 W

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 90 91** LED POWER SUPPLY 350mA-DC / 15W

2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 40




**300 90 110** LED POWER SUPPLY 350mA-DC / 10W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42




**300 90 116** LED POWER SUPPLY 350mA-DC / 18W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




**21012 0515** LED POWER SUPPLY MULTI POWER DIM5

1(1)

Dimtype: DALI

Cutout dimension (mm): 55




**21012 0520** LED POWER SUPPLY 350mA-DC / 8W

1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 47




**21012 0575** LED POWER SUPPLY MULTI POWER DIM5

2->3(2)

Dimtype: DALI

Cutout dimension (mm): 55

### Mounting kits



**15212 2030** MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.

Cutout dimension (mm): 105

# DELTALIGHT

## SPY 52 TRIMLESS HE 92740

19807 9230 W

### Mounting kits stretched ceiling

---



**15212 0080** MOUNTING KIT SPY 39/52 TRIMLESS CSC




**15212 0160** MOUNTING KIT SPY 39/52 TRIMLESS WSC



### Mounting kits side air + light

---




**29810 0030** MOUNTING KIT SIDE AIR 103

Cutout dimension (mm): 168



### Mounting kits top air + light

---




**29810 0230** MOUNTING KIT TOP AIR 103

Cutout dimension (mm): 135



### Mounting kits side air only

---




**29810 0100** MOUNTING KIT SIDE AIR ONLY 1

Cutout dimension (mm): 168



### Mounting kits top air only

---



**29810 0200** MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135



# DELTALIGHT

## SPY 52 TRIMLESS HE 92740

19807 9230 W

### Mounting kits no air

---



**29810 0070** MOUNTING KIT NO AIR 103

Cutout dimension (mm): 168

### Finish your product

---



**19810 0100 B** SPY 52 TUBE B

**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG

**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W

Notes: