
DELTALIGHT




# SPY 52 TRIMLESS HE 92740

**REFERENCE** 19807 9230 W

AVAILABLE IN
**BLACK** 19807 9230 B
**FLEMISH BRONZE** 19807 9230 FBR
**FLEMISH GOLD** 19807 9230 FG
**GOLD COLOURED** 19807 9230 GC
**WHITE** 19807 9230 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - Ø KIT |
| **RECESSED DEPTH (MM)** | 80 |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.4 |
| **ADJUSTABILITY** | 0° to 45° swiveling, 355° rotatable |
| **INFORMATION** | LENS WFL-40°<br>EXCL.LED POWER SUPPLY 350mA-DC |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | D |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 40° |
| **LED TECHNICS (LIGHT SOURCE)** | 905lm // 6W // 150lm/W |
| **LED TECHNICS (LUMINAIRE)** | 704lm // 6,9W // 102lm/W |

**Remarks**

High Efficacy : > 100lm/W

**Requirements**

SPY 52 TUBE
MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.
MOUNTING KIT AIR 103
LED POWER SUPPLY 350mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : **19807_XXX0_HAND.pdf**

# SPY 52 TRIMLESS HE 92740


19807 9230 W

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit | |
|---|---|---|
|  **System ceiling** | 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A. | Required |
|  **Plasterboard** | 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A. | Required |
|  **Stucanet** | 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A. | Required |
|  **Concrete + plaster** | 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A. | Required |
|  **Lintel + plaster** | 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A. | Required |
|  **Hollow-core slab + plaster** | 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A. | Required |
|  **Stretched ceiling** | 15212 0080 - MOUNTING KIT SPY 39/52 TRIMLESS CSC | Required |
| | 15212 0160 - MOUNTING KIT SPY 39/52 TRIMLESS WSC | Required |
|  **Ventilation in plasterboard** | 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1 | Required |
| | 29810 0030 - MOUNTING KIT SIDE AIR 103 | Required |
| | 29810 0070 - MOUNTING KIT NO AIR 103 | Required |
|  **Ventilation in concrete + plaster** | 29810 0200 - MOUNTING KIT TOP AIR ONLY 1 | Required |
| | 29810 0230 - MOUNTING KIT TOP AIR 103 | Required |
| | 29810 0070 - MOUNTING KIT NO AIR 103 | Required |

## FINISH YOUR SPECIFICATION

### Emergency units



**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

**Cutout dimension (mm): 27**

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

DELTALIGHT

# SPY 52 TRIMLESS HE 92740


19807 9230 W

## LED power supplies

## # of Fixtures

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**300 90 91** LED POWER SUPPLY 350mA-DC / 15W — 2(1)

**Dimtype: non-dimmable**


**Cutout dimension (mm): 40**




**300 90 110** LED POWER SUPPLY 350mA-DC / 10W DIM8 — 1

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 42**




**300 90 116** LED POWER SUPPLY 350mA-DC / 18W DIM8 — 2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0515** LED POWER SUPPLY MULTI POWER DIM5 — 1(1)

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**21012 0520** LED POWER SUPPLY 350mA-DC / 8W — 1(0)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 47**





**21012 0575** LED POWER SUPPLY MULTI POWER DIM5 — 2->3(2)

**Dimtype: DALI**

**Cutout dimension (mm): 55**

## Mounting kits





**15212 2030** MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.

**Cutout dimension (mm): 105**

# SPY 52 TRIMLESS HE 92740

19807 9230 W

## Mounting kits stretched ceiling





**15212 0080** MOUNTING KIT SPY 39/52 TRIMLESS CSC




**15212 0160** MOUNTING KIT SPY 39/52 TRIMLESS WSC


## Mounting kits side air + light




**29810 0030** MOUNTING KIT SIDE AIR 103

**Cutout dimension (mm): 168**


## Mounting kits top air + light




**29810 0230** MOUNTING KIT TOP AIR 103

**Cutout dimension (mm): 135**


## Mounting kits side air only




**29810 0100** MOUNTING KIT SIDE AIR ONLY 1

**Cutout dimension (mm): 168**

## Mounting kits top air only




**29810 0200** MOUNTING KIT TOP AIR ONLY 1

**Cutout dimension (mm): 135**

DELTALIGHT

# SPY 52 TRIMLESS HE 92740

19807 9230 W


## Mounting kits no air




**29810 0070** MOUNTING KIT NO AIR 103

**Cutout dimension (mm): 168**

## Finish your product




**19810 0100 B** SPY 52 TUBE B

**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG

**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W

Notes: