



MICROSPY 39 C 93045

279 773 811 931 W

AVAILABLE IN

BLACK 279 773 811 931 B

BRUSHED ALU 279 773 811 931 BRA



BRUSHED ANTHRACITE 279 773 811 931 BRAT

BRUSHED COPPER 279 773 811 931 BRCU

BRUSHED GOLD 279 773 811 931 BRG

BRUSHED OLD BRONZE 279 773 811 931 BROB

WHITE 279 773 811 931 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm ² / 1,6m

Electrical info

ELECTRICAL	110-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	530lm // 6,7W // 79lm/W


Options

CONNECTION TRIMLESS

For detailed installation instructions, please consult the manual : [279_773_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)

Notes: