
DELTALIGHT




# MICROSPY 39 C 93045

**REFERENCE** 279 773 811 931 W

AVAILABLE IN
**BLACK** 279 773 811 931 B
**BRUSHED ALU** 279 773 811 931 BRA
**BRUSHED ANTHRACITE** 279 773 811 931 BRAT
**BRUSHED COPPER** 279 773 811 931 BRCU
**BRUSHED GOLD** 279 773 811 931 BRG
**BRUSHED OLD BRONZE** 279 773 811 931 BROB
**WHITE** 279 773 811 931 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Suspended |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.7 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | REFLECTOR WFL-45°<br>INCL.LED POWER SUPPLY 350mA-DC<br>INCL.1 x CABLE 2 x 0.75mm² / 1,6m |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 110-240V / 50-60Hz |
| **CLASS** | II |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | non-dimmable |
| **ENERGY CLASS** | C |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| **TM-30 VALUES** | Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 45° |
| **LED TECHNICS (LIGHT SOURCE)** | 787lm // 5,8W // 135lm/W |
| **LED TECHNICS (LUMINAIRE)** | 530lm // 7W // 79lm/W |

**Options**

CONNECTION TRIMLESS

For detailed installation instructions, please consult the manual : **279_773_811_XXX_HAND.pdf**


DELTALIGHT

# MICROSPY 39 C 93045

279 773 811 931 W


## FINISH YOUR SPECIFICATION

### Suspension parts




**15229 0010 B** CABLE CLAMP B ☐

### Electric connection parts




**328 10 03** CONNECTION TRIMLESS O.F.A. ☐

**Cutout dimension (mm): 62 (CONCRETE: 102)**

Notes: