


LED POWER SUPPLY 1200mA-DC / 70W DIM1

300 90 132



[Bekijk op website](#)



Image may differ from the actual product

Algemene info	
LOCATIE	binnen
ZAAGMAAT/OPENING (MM)	rond - 80
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.4
INFO	CURRENT CONTROLLED OUTPUT: 1200mA / 70W / 58V-DC $\lambda > 0,9$ Inrush current : 35A - 1000 μ s @ 230V-AC Max. 8 units on circuit breaker B 16A
Elektrische info	
KLASSE	II
DIM TYPE	1-10V

Voor gedetailleerde montage gegevens, consulteer de handleiding : [300_90_132_HAND.pdf](#)

WAAR GEBRUIKT

321 112 92	SUPERLOOP HC 120 SBL 927
321 112 93	SUPERLOOP HC 120 SBL 930
321 117 92	SUPERLOOP HC 170 SBL 927
321 117 93	SUPERLOOP HC 170 SBL 930
321 212 93	SUPERLOOP HC 120 SPR 930
321 217 93	SUPERLOOP HC 170 SPR 930
321 412 92	SUPERLOOP VR 120 SBL 927
321 412 93	SUPERLOOP VR 120 SBL 930
321 512 92	SUPERLOOP VC 120 SBL 927
321 512 93	SUPERLOOP VC 120 SBL 930
20563 9200	SUPERLOOP PLUS HC 120 SBL 927
20563 9300	SUPERLOOP PLUS HC 120 SBL 930
20571 9200	SUPERLOOP HC SBL OVAL M 927
20571 9300	SUPERLOOP HC SBL OVAL M 930
20574 9200	SUPERLOOP SLIM IN 120 SBL 927
20574 9300	SUPERLOOP SLIM IN 120 SBL 930
20575 9200	SUPERLOOP SLIM IN 170 SBL 927
20575 9300	SUPERLOOP SLIM IN 170 SBL 930
20578 9200	SUPERLOOP SLIM OUT 120 SBL 927
20578 9300	SUPERLOOP SLIM OUT 120 SBL 930
20579 9200	SUPERLOOP SLIM OUT 170 SBL 927

DELTALIGHT

LED POWER SUPPLY 1200mA-DC / 70W DIM1

300 90 132

20579 9300	SUPERLOOP SLIM OUT 170 SBL 930
20582 9200	SUPERLOOP SLIM DOWN 120 SBL 927
20582 9300	SUPERLOOP SLIM DOWN 120 SBL 930

Notes: