
DELTALIGHT




SPY 52 TRIMLESS HE 93020

REFERENCE 19807 9320 B

AVAILABLE IN
BLACK 19807 9320 B
FLEMISH BRONZE 19807 9320 FBR
FLEMISH GOLD 19807 9320 FG
GOLD COLOURED 19807 9320 GC
WHITE 19807 9320 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K / 945lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	945lm // 6W // 157lm/W
LED TECHNICS (LUMINAIRE)	765lm // 7W // 111lm/W

Remarks

High Efficacy : > 100lm/W

Requirements

SPY 52 TUBE
MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.
MOUNTING KIT AIR 103
LED POWER SUPPLY 350mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : **19807_XXX0_HAND.pdf**

SPY 52 TRIMLESS HE 93020


19807 9320 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 **Plasterboard**	15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 **Stucanet**	15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 **Concrete + plaster**	15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 **Lintel + plaster**	15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 **Hollow-core slab + plaster**	15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 **Stretched ceiling**	15212 0080 - MOUNTING KIT SPY 39/52 TRIMLESS CSC	Required
	15212 0160 - MOUNTING KIT SPY 39/52 TRIMLESS WSC	Required
 **Ventilation in plasterboard**	29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	29810 0030 - MOUNTING KIT SIDE AIR 103	Required
	29810 0070 - MOUNTING KIT NO AIR 103	Required
 **Ventilation in concrete + plaster**	29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
	29810 0230 - MOUNTING KIT TOP AIR 103	Required
	29810 0070 - MOUNTING KIT NO AIR 103	Required

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B ☐

Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W ☐

DELTALIGHT

SPY 52 TRIMLESS HE 93020


19807 9320 B

LED power supplies

# of Fixtures

Min current | Max current


# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 91 LED POWER SUPPLY 350mA-DC / 15W — 2(1)

Dimtype: non-dimmable


Cutout dimension (mm): 40



300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 — 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 42



300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 — 2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0515 LED POWER SUPPLY MULTI POWER DIM5 — 1(1)

Dimtype: DALI

Cutout dimension (mm): 55



21012 0520 LED POWER SUPPLY 350mA-DC / 8W — 1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 47




21012 0575 LED POWER SUPPLY MULTI POWER DIM5 — 2->3(2)

Dimtype: DALI

Cutout dimension (mm): 55

Mounting kits




15212 2030 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.

Cutout dimension (mm): 105

SPY 52 TRIMLESS HE 93020

19807 9320 B

Mounting kits stretched ceiling




15212 0080 MOUNTING KIT SPY 39/52 TRIMLESS CSC



15212 0160 MOUNTING KIT SPY 39/52 TRIMLESS WSC


Mounting kits side air + light



29810 0030 MOUNTING KIT SIDE AIR 103

Cutout dimension (mm): 168


Mounting kits top air + light



29810 0230 MOUNTING KIT TOP AIR 103

Cutout dimension (mm): 135


Mounting kits side air only



29810 0100 MOUNTING KIT SIDE AIR ONLY 1

Cutout dimension (mm): 168

Mounting kits top air only



29810 0200 MOUNTING KIT TOP AIR ONLY 1


Cutout dimension (mm): 135

DELTALIGHT

SPY 52 TRIMLESS HE 93020

19807 9320 B


Mounting kits no air



29810 0070 MOUNTING KIT NO AIR 103

Cutout dimension (mm): 168

Finish your product



19810 0100 B SPY 52 TUBE B

19810 0100 FBR SPY 52 TUBE FBR

19810 0100 FG SPY 52 TUBE FG

19810 0100 GC SPY 52 TUBE GC

19810 0100 W SPY 52 TUBE W

Notes: