
DELTALIGHT




SPLIT-IT SPY FOCUS LP 930

REFERENCE 18428 9300 W

AVAILABLE IN
BLACK 18428 9300 B
WHITE 18428 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
INFORMATION	ADJUSTABLE ADJUSTABLE BEAM 8°-43° EXCL.LED POWER SUPPLY 48V-DC EXCL.LED POWER CONVERTER 48V TO 500-700mA-DC PRO

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6-12,5W / CRI>90 (R9: 52) / 3000K / 1018-1378lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	8°-43°
LED TECHNICS (LIGHT SOURCE)	1378lm // 12,5W // 110lm/W
LED TECHNICS (LUMINAIRE)	565lm // 14,4W // 39lm/W

Requirements

LED POWER CONVERTER 48V-DC to 500 mA-DC
LED POWER CONVERTER 48V-DC to 700 mA-DC
LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING 48V-DC

For detailed installation instructions, please consult the manual : **18428_XXXX_HAND.pdf**


DELTALIGHT

SPLIT-IT SPY FOCUS LP 930


18428 9300 W

FINISH YOUR SPECIFICATION

Current supply



416 99 00 THROUGH WIRING 48V-DC SPLIT-IT PRO ☐




416 99 01 THROUGH WIRING 48V-DC SPLIT-IT ON ☐

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 48 500 PRO ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM1 2 ☐

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 500 PRO ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM5 2 ☐

Dimtype: DALI


Cutout dimension (mm): 45



300 48 500 PRO WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO WDL 2 ☐

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 48 700 PRO ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM1 2 ☐

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 700 PRO ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5 2 ☐

Dimtype: DALI

Cutout dimension (mm): 45

SPLIT-IT SPY FOCUS LP 930


18428 9300 W



300 48 700 PRO WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO WDL — 2

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 2 | 2 | 2

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 4(4) | 4(3)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 3(2) | 2(1) | 2(1)

Dimtype: 1-10V or push button


Cutout dimension (mm): 72



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 2(1) | 2(1)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 6(4) | 4(3)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 2(2) | 1(1)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 2(2) | 1(1)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV — 3->4 | 2->4 | 2->4

Dimtype: non-dimmable

Cutout dimension (mm): 90




21012 0010 LED POWER SUPPLY MULTI POWER — 2 | 2

Dimtype: non-dimmable

Cutout dimension (mm): 50

SPLIT-IT SPY FOCUS LP 930


18428 9300 W



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 3 | 2

Dimtype: 1-10V


Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 3 | 3

Dimtype: DALI


Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 4(4) | 4(3) | 3(3)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 3 | 2

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 2->2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 1 | 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 2->3 | 2->2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 2 | 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 1


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40

DELTALIGHT

SPLIT-IT SPY FOCUS LP 930


18428 9300 W



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 — 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 40



21012 0328 LED POWER SUPPLY 700mA / 15W DIM8 — 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 40



21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 — 2(1)

Dimtype: non-dimmable


Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 — 2(1)

Dimtype: non-dimmable


Cutout dimension (mm): 60



21032 0375 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 30




21032 0385 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 30

COMPATIBLE COMPOSABLES

SPLIT-IT PRO profile	Available Colours
 **372 01 00** SPT PRO - PROFILE	

Notes: