
DELTALIGHT




M26L - HEDRA L 93033 DIM5

REFERENCE 23253 9325 BBR

AVAILABLE IN
BLACK BRONZE 23253 9325 BBR
GOLD COLOURED 23253 9325 GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	547lm // 9,9W // 55lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

VIZIR TUBE
LED POWER SUPPLY 48V-DC

Accessories

VIZIR HONEYCOMB
VIZIR SOFTENING LENS

DELTALIGHT

M26L - HEDRA L 93033 DIM5

23253 9325 BBR

For detailed installation instructions, please consult the manual : **23253_XXXX_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W — 7 ☐


Dimtype: non-dimmable

Cutout dimension (mm): 75




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 8 ☐

Dimtype: non-dimmable




300 89 48 150 LED POWER SUPPLY 48V-DC / 150W — 12 ☐

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 19 ☐


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 8 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 16 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

M26L - HEDRA L 93033 DIM5


23253 9325 BBR

Power box

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



23377 0010 B SLM26L - POWERBOX 48V-DC / 96W B — 8

Dimtype: non-dimmable

23377 0010 W SLM26L - POWERBOX 48V-DC / 96W W — 8




23377 0020 B SLM26L - MID POWERBOX 48V-DC / 96W B — 8


Dimtype: non-dimmable

23377 0020 W SLM26L - MID POWERBOX 48V-DC / 96W W — 8

Light altering devices




473 03 01 B VIZIR HONEYCOMB B



473 03 04 VIZIR SOFTENING LENS

Finish your product



473 01 00 B VIZIR TUBE B

473 01 00 FBR VIZIR TUBE FBR





473 01 00 FG VIZIR TUBE FG





M26L - HEDRA L 93033 DIM5

23253 9325 BBR

473 01 00 W VIZIR TUBE W

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
 **23358 0000** SLM26L - PROFILE	
 **23358 0010** SLM26L - PROFILE 1m	
 **23358 0020** SLM26L - PROFILE 2m	
 **23358 0030** SLM26L - PROFILE 3m	

SHIFTLINE M35R profile	Available Colours
 **23375 0000** SLM35R - PROFILE	
 **23375 0010** SLM35R - PROFILE 1m	
 **23375 0020** SLM35R - PROFILE 2m	
 **23375 0030** SLM35R - PROFILE 3m	

DELTALIGHT

M26L - HEDRA L 93033 DIM5

23253 9325 BBR

Notes: