



ENTERO RD-L WALLWASH TW 965



28476 9000 B

AVAILABLE IN

NOIR 28476 9000 B

COULEUR OR 28476 9000 GC

BLANC 28476 9000 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 112
RECESSED DEPTH (MM)	160
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.67
ADJUSTABILITY	non réglable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1690lm // 20,5W // 83lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

Options

ENTERO RD-L MOUNTING SET S2

For detailed installation instructions, please consult the manual : [28476_XXX0_HAND.pdf](#)

ENTERO RD-L WALLWASH TW 965


28476 9000 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit		
 System ceiling	-		
 Plasterboard	-		
 Stucanet	-		
 Wood	-		
 Concrete		28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 Concrete + plaster		28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 Lintel + plaster		28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 Hollow-core slab		28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 Hollow-core slab + plaster		28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 Stretched ceiling	-		

FINISH YOUR SPECIFICATION

les alimentations led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current


	21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5	1
Dimtype: DALI		
Cutout dimension (mm): 85		

DELTALIGHT

ENTERO RD-L WALLWASH TW 965

28476 9000 B

Mounting set S2



28500 0210 ENTERO RD-L MOUNTING SET S2



Notes: