



COMPO L 93010

9 15735 9310 B



AVAILABLE IN

BLACK 9 15735 9310 B

CHROMED 9 15735 9310 C

DARK CHROMED 9 15735 9310 DC

WHITE 9 15735 9310 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.46
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	Accessories are not applicable with Super Spot except Honeycomb Single use B

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,3W / CRI>90 / 3000K / 583lm
TM-30 VALUES	rf: 90 / Rg: 99
BEAMANGLE	10°
LED TECHNICS (LIGHT SOURCE)	583lm // 5,3W // 110lm/W
LED TECHNICS (LUMINAIRE)	353lm // 6,1W // 58lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO L HONEYCOMB SINGLE USE B
COMPO L LINEAR SPREAD LENS
COMPO L SPREAD LENS
COMPO L SOFTENING LENS
COMPO L GLASS SBL

For detailed installation instructions, please consult the manual : [9_15735_XXX0_HAND.pdf](#)

DELTALIGHT

COMPO L 93010

9 15735 9310 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current


15710 3200	LED POWER SUPPLY MULTIPOWER 15W NO DIM 300mA	1->2	
15710 3600	LED POWER SUPPLY MULTIPOWER 20W NO DIM 500mA	1	
15710 3700	LED POWER SUPPLY MULTIPOWER 10W DIM8 300mA	1	
15710 4200	LED POWER SUPPLY MULTIPOWER 20W DIM8 500mA	1	
15710 4400	LED POWER SUPPLY MULTIPOWER 12W DIM1 300mA	1->2	
15710 4700	LED POWER SUPPLY MULTIPOWER 20W DIM1 500mA	1	
15710 5200	LED POWER SUPPLY MULTIPOWER 12W DALI DT6 300mA	1->2	
Dimtype: DALI			
15710 5400	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA	1	
Dimtype: DALI			

DELTALIGHT

COMPO L 93010

9 15735 9310 B

Mounting kits



15710 0030 B MOUNTING KIT COMPO L TRIM B

☐

Cutout dimension (mm): 92



15710 0060 MOUNTING KIT COMPO L TRIMLESS

☐

Cutout dimension (mm): 92

Light altering devices

15710 2100 B COMPO L HONEYCOMB SINGLE USE B

☐

15710 2110 COMPO L LINEAR SPREAD LENS

☐

Cutout dimension (mm): 42

15710 2120 COMPO L SPREAD LENS

☐

Cutout dimension (mm): 42

15710 2130 COMPO L SOFTENING LENS

☐

Cutout dimension (mm): 42

15710 2140 COMPO L GLASS SBL

☐

Cutout dimension (mm): 42

Notes: