
DELTALIGHT




SUPERLOOP VR 120 SBL 930

REFERENCE 321 412 93 FG

AVAILABLE IN
BLACK 321 412 93 B
FLEMISH BRONZE 321 412 93 FBR
FLEMISH GOLD 321 412 93 FG
WHITE 321 412 93 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 900-1200mA-DC INCL.1 x SUSPENSION TUBE 0.5m

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 36,4-50,3W / CRI>90 (R9: 59) / 3000K / 5022-6665lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	6665lm // 50,3W // 132lm/W
LED TECHNICS (LUMINAIRE)	4005lm // 57,8W // 69lm/W

Requirements

LED POWER SUPPLY 900 / 1200mA-DC DIM

For detailed installation instructions, please consult the manual : **321_412_93_HAND.pdf**

DELTALIGHT

SUPERLOOP VR 120 SBL 930

321 412 93 FG


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 129 LED POWER SUPPLY 900mA-DC / 60W DIM5 — 1 ☐

Dimtype: DALI


Cutout dimension (mm): 84



300 90 130 LED POWER SUPPLY 1200mA-DC / 60W DIM5 — 1 ☐

Dimtype: DALI

Cutout dimension (mm): 95



300 90 132 LED POWER SUPPLY 1200mA-DC / 70W DIM1 — 1 ☐

Dimtype: 1-10V

Cutout dimension (mm): 80

Notes: