

LOGIC LINEAR ON 880 94040 DIM5

30835 9435 A

AVAILABLE IN



ALU GREY 30835 9435 A

BLACK 30835 9435 B

FLEMISH BRONZE OUTDOOR 30835 9435 FBRX

ANTHRACITE 30835 9435 N

WHITE 30835 9435 W



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2
INFORMATION	16 x LENS WFL-40° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 64) / 4000K / 3898lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	3898lm // 28,8W // 131lm/W
LED TECHNICS (LUMINAIRE)	2967lm // 33,1W // 90lm/W

Requirements

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING SET IP68






DELTALIGHT

LOGIC LINEAR ON 880 94040 DIM5

30835 9435 A

For detailed installation instructions, please consult the manual : [30835_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
		Min current Max current
<p> # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</p>		
	21032 0390 LED POWER SUPPLY 48V-DC / 90W Dimtype: non-dimmable Cutout dimension (mm): 75	2 <input type="checkbox"/>
Fixation components		
	30810 0040 LOGIC LINEAR 880 BOX EXTEND	<input type="checkbox"/>
	30810 0040 INOX WALL BRACKET SET 60 INOX	<input type="checkbox"/>
	30810 0040 N WALL BRACKET SET 60 N	<input type="checkbox"/>
	30810 0050 INOX WALL BRACKET SET 100 INOX	<input type="checkbox"/>
	30810 0050 N WALL BRACKET SET 100 N	<input type="checkbox"/>
	30810 0060 INOX WALL BRACKET SET 200 INOX	<input type="checkbox"/>
	30810 0060 N WALL BRACKET SET 200 N	<input type="checkbox"/>

DELTALIGHT

LOGIC LINEAR ON 880 94040 DIM5

30835 9435 A



30810 0070 INOX FLOOR BRACKET SET INOX



Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m



30810 0090 IP68 CABLE + CONNECTOR 5P - 2m



30810 0110 THROUGH WIRING SET IP68 880



Notes: