
DELTALIGHT




SPY 52 ON 2 SOFT 93020 DIM8

REFERENCE 19832 9028 B-B

AVAILABLE IN
BLACK-BLACK 19832 9028 B-B
FULL WHITE 19832 9028 FW
WHITE-WHITE 19832 9028 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	2 x REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC Optional REFLECTORS 30° & 45° available

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm)
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1246lm // 12W // 105lm/W
LED TECHNICS (LUMINAIRE)	781lm // 14W // 57lm/W

Requirements

SPY 52 TUBE

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

DELTALIGHT


SPY 52 ON 2 SOFT 93020 DIM8

19832 9028 B-B


For detailed installation instructions, please consult the manual : **19832_XXX8_HAND.pdf**

FINISH YOUR SPECIFICATION


Light altering devices



19810 0010 B HONEYCOMB 42 SINGLE USE B ☐




19810 0020 LINEAR SPREAD LENS 42 ☐




19810 0030 SPREAD LENS 42 ☐



19810 0040 SOFTENING LENS 42 ☐




19810 0050 GLASS SBL 42 ☐



19810 0060 B HONEYCOMB 42 DOUBLE USE B ☐

Finish your product



19810 0100 B SPY 52 TUBE B ☐




DELTALIGHT

SPY 52 ON 2 SOFT 93020 DIM8

19832 9028 B-B

19810 0100 FBR	SPY 52 TUBE FBR	☐
19810 0100 FG	SPY 52 TUBE FG	☐
19810 0100 GC	SPY 52 TUBE GC	☐
19810 0100 W	SPY 52 TUBE W	☐

Replaceable reflector / lens

	**19810 0180** SPY 52 REFLECTOR 20°	☐
	**19810 0190** SPY 52 REFLECTOR 45°	☐
	**19810 0240** SPY 52 REFLECTOR 30°	☐

Notes: