



OML50 - PRISMATIC LENS DU HO
2296mm 930

31637 9300 B

BESCHIKBAAR IN
ZWART 31637 9300 B

 [Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	3.1
INFO	INCL LED POWER SUPPLY CABLING 1 CIRCUIT
Elektrische info	
ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 54,3W / CRI>90 (R9: 50) / 3000K / 8330lm UP: LED cluster 42,3W / CRI>90 (R9: 50) / 3000K / 6115lm
TM-30 WAARDEN	Rf: 92 / Rg: 100
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 8330lm // 54,3W // 153lm/W UP: 6115lm // 42,3W // 145lm/W

Notes: