
DELTALIGHT




SUPERNOVA LINE 95 TW DOWN-UP DIM5

REFERENCE 274 96 09 26 ED5 B

AVAILABLE IN
BLACK 274 96 09 26 ED5 B
WHITE 274 96 09 26 ED5 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	13
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY - DALI (DT6) CABLING 2 CIRCUITS 4 DALI CONTROL CHANNELS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm²

Electrical info	
ELECTRICAL	120-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K : LED cluster 112W / CRI>80 / 2700K - 5700K / 10520lm UP @ 2700K : LED cluster 33W / CRI>80 / 2700K - 5700K / 2748lm Or DOWN @ 5700K : LED cluster 112W / CRI>80 / 2700K - 5700K / 12103lm UP @ 5700K : LED cluster 33W / CRI>80 / 2700K - 5700K / 3020lm
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 10520 lm // 112 W // 94 lm/W UP @ 2700K: 2748 lm // 33 W // 83 lm/W Or DOWN @ 5700K: 12103 lm // 112 W // 108 lm/W UP @ 5700K: 3020 lm // 33 W // 92 lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2700K: 8016lm // 129W // 62lm/W UP @ 2700K: 2402lm // 38W // 63lm/W Or DOWN @ 5700K: 9198lm // 129W // 71lm/W UP @ 5700K: 2639lm // 38W // 70lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


SUPERNOVA LINE 95 TW DOWN-UP DIM5

274 96 09 26 ED5 B

For detailed installation instructions, please consult the manual : **274_96_09_26_ED5_HAND.pdf**

FINISH YOUR SPECIFICATION


Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W




203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B

204 00 62 W COVERSET R 62 W







204 00 90 ANO COVERSET R 90 ANO

DELTALIGHT

SUPERNOVA LINE 95 TW DOWN-UP DIM5

274 96 09 26 ED5 B


	204 00 90 B	COVERSET R 90 B	☐
	204 00 90 W	COVERSET R 90 W	☐
	**204 00 100 ANO**	COVERSET R 100 ANO	☐
	204 00 100 B	COVERSET R 100 B	☐
	204 00 100 W	COVERSET R 100 W	☐
	**204 62 62 ANO**	COVERSET S 62 ANO	☐
	204 62 62 B	COVERSET S 62 B	☐
	204 62 62 W	COVERSET S 62 W	☐
	**204 80 80 ANO**	COVERSET S 80 ANO	☐
	204 80 80 B	COVERSET S 80 B	☐
	204 80 80 W	COVERSET S 80 W	☐
	**204 90 90 ANO**	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐
	204 90 90 W	COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA LINE 95 TW DOWN-UP DIM5


274 96 09 26 ED5 B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: