

ODRON



Don't be fooled: Odron may look peculiar at first sight, nevertheless its specific design is intended to create a compact yet powerful lighting solution. A second look puts everything in perspective: the flat design of the disc in combination with the shallow base results in a highly functional luminaire within a limited diameter of less than 2.5".

Specification	
LED Aperture:	1 1/16"
Ceiling Cutout:	2"
Optic:	28° and 41°
Adjustability:	Adjustable 0-90° / 355°
Rating:	Damp

Performance	
LED Maintenance:	L70>50,000h
McAdam Step:	1
CRI:	90
*MP:	6.1W
*HP:	9W

Delivered Lumens	2700K	3000K	3500K
Odron MP:	644Lm	649Lm	665Lm
Odron HP:	894Lm	902Lm	923Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: ODR-MPFC35A-W-W-GC-CLRS-RMTD8-120

Luminaire	Power*	Optic	CCT	Function	Finish	Inner Finish	Style	Installation	Application	Controls***					
ODR ODRON	MP Medium Power	FC Field changeable reflector, both 28° & 41° included	27 2700K	A Adjustable	B-B Black-Black	GC Gold Colored plate	CL Clip semi- recessed	FL Flush kit for mud into drywall	IAT ⁽¹⁾ New Construction IC AIRTIGHT	D1-UNV 0-10V dim 120-277V					
			30 3000K								W-W White-White	NA No optional accessory	RS Surface trim for rigid surface	IAT_RMT New Construction IC AIRTIGHT + Remote Power Supply	D8-120 FE ELV dim 120V
			35 3500K												

¹ Only available with Power HP.

*** Contact factory for additional dimming options.

Related Products

M-Odron, Bowie, Pion




Finish Options

ODRON



Photometric Data

ODRON




Installation Options

IC AIRTIGHT

S-SMALL:
A:12"-5/8 x **B:**11"-1/16 x **C:**4"-13/16
A:323mm x **B:**281mm x **C:**122mm

- Low Profile under 5" Height
- New Construction Airtight
- For use in insulated ceiling
- Chicago Plenum
- ETL Listed
- Hangerbar expand to 24"-23/32 or 15"-3/32 - reduce to 12"23/32 or 9"- 1/32
- Damp rated
- Patented System for easy driver servicing from room side

FL - FLUSH MOUNT KIT



REMOTE DRIVER (With Control D8)

A: 8" x **B:** 2"-1/2 x **C:** 2"-1/2
A: 203mm x **B:** 64mm x **C:** 64mm

- For Remote application
- ETL Listed
- Damp rated

REMOTE DRIVER (With Control D1)

A: 8" x **B:** 2"-3/16 x **C:** 4"-1/4
A: 203mm x **B:** 72mm x **C:** 108mm

- For Remote application
- ETL Listed
- Damp rated



Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

D8 (With Housing IAT_RMT or RMT - 2 Fixtures)

- Dimming Control Phase Control
- Dimming Range 20-100%
- Dim to off yes
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥80
- THD @ Full Load <10%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.