
DELTALIGHT




SPIX M 24V 92730

REFERENCE 29716 9230 PGR

AVAILABLE IN
ANTHRACITE 29716 9230 N
PINE GREEN 29716 9230 PGR





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK05
WEIGHT (KG)	0.6
ADJUSTABILITY	90° swiveling, 360° rotatable
INFORMATION	LENS FL-30° EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output)

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,2W / CRI>90 (R9: 56) / 2700K / 677lm
TM-30 VALUES	Rf: 91 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	677lm // 8,2W // 83lm/W
LED TECHNICS (LUMINAIRE)	454lm // 9W // 48lm/W

Requirements

LED POWER SUPPLY 24V-DC

Accessories

KAP STRIPER

For detailed installation instructions, please consult the manual : **29716_XXX0_HAND.pdf**

DELTALIGHT

SPIX M 24V 92730

29716 9230 PGR


FINISH YOUR SPECIFICATION

LED power supplies

# of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W — 15 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 75



21012 0160 LED POWER SUPPLY 24V-DC / 24W — 2 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 55



21012 0171 LED POWER SUPPLY 24V-DC / 60W DIM1 — 6 ☐

Dimtype: 1-10V


Cutout dimension (mm): 61



21012 0181 LED POWER SUPPLY 24V-DC / 90W DIM1 — 9 ☐

Dimtype: 1-10V

Cutout dimension (mm): 70




21012 0191 LED POWER SUPPLY 24V-DC / 120W DIM1 — 12 ☐

Dimtype: 1-10V

Cutout dimension (mm): 70

Miscellaneous control equipment




21032 0320 AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM) ☐

DELTALIGHT

SPIX M 24V 92730

29716 9230 PGR

Light altering devices



223 00 10 B KAP STRIPER B

Notes: