



ENTERO RD-S TRIMLESS WALLWASH TW 940



28465 9000 W

AVAILABLE IN

NOIR 28465 9000 B

COULEUR OR 28465 9000 GC

BLANC 28465 9000 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
RECESSED DEPTH (MM)	95
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.14
ADJUSTABILITY	non réglable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	979lm // 9W // 109lm/W
LED TECHNICS (LUMINAIRE)	796lm // 10,4W // 77lm/W

Requirements

MOUNTING KIT ENTERO ROUND S

MOUNTING KIT AIR 105

LED POWER SUPPLY 500mA-DC TW (Remote)

For detailed installation instructions, please consult the manual : [28465_XXX0_HAND.pdf](#)

DELTA LIGHT


ENTERO RD-S TRIMLESS WALLWASH TW 940

28465 9000 W

CEILING COMPATIBILITY			
Ceiling Type	Mounting Kit		
 System ceiling	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required		
 Plasterboard	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required		
 Stucanet	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required		
 Concrete + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required		
 Lintel + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required		
 Hollow-core slab + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required		
 Stretched ceiling	 28400 0070 - MOUNTING KIT ENTERO RD-S CSC Required		
	 28400 0130 - MOUNTING KIT ENTERO RD-S WSC Required		
 Ventilation in plasterboard	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1 Required		
	 29810 0120 - MOUNTING KIT NO AIR 105 Required		
	 29810 0110 - MOUNTING KIT SIDE AIR 105 Required		
 Ventilation in concrete + plaster	 29810 0120 - MOUNTING KIT NO AIR 105 Required		
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1 Required		
	 29810 0130 - MOUNTING KIT TOP AIR 105 Required		

FINISH YOUR SPECIFICATION


les alimentations led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current

	21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5	2
Dimtype: DALI Cutout dimension (mm): 85		

ENTERO RD-S TRIMLESS WALLWASH TW 940

28465 9000 W

kit de montage




28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.

☐

Cutout dimension (mm): 105

kit de montage plafond tendu




28400 0070 MOUNTING KIT ENTERO RD-S CSC

☐

28400 0130 MOUNTING KIT ENTERO RD-S WSC

☐


kit de montage - side air + light



29810 0100 MOUNTING KIT SIDE AIR ONLY 1

☐

Cutout dimension (mm): 168




29810 0110 MOUNTING KIT SIDE AIR 105

☐

Cutout dimension (mm): 168

kit de montage - top air + light



29810 0130 MOUNTING KIT TOP AIR 105

☐


Cutout dimension (mm): 135

DELTALIGHT

ENTERO RD-S TRIMLESS WALLWASH TW 940

28465 9000 W

kit de montage - top air only




29810 0200 MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135



kit de montage - no air



29810 0120 MOUNTING KIT NO AIR 105

Cutout dimension (mm): 168



Notes: