DELTALIGHT

NIME II 92752

REFERENCE 26414 9230 W

AVAILABLE IN
BLACK 26414 9230 B
WHITE 26414 9230 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 67
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	9,5-12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	LENS WFL-52° EXCL.LED POWER SUPPLY 350-700mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9-8,2W / CRI>90 (R9: 56) / 2700K / 385-677lm
TM-30 VALUES	Rf: 91 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	52°
LED TECHNICS (LIGHT SOURCE)	677lm // 8,2W // 83lm/W
LED TECHNICS (LUMINAIRE)	437lm // 9,4W // 46lm/W

Requirements

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM

For detailed installation instructions, please consult the manual : **26414_XXX0_HAND.pdf**

DELTALIGHT

NIME II 92752

26414 9230 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
System ceiling	-
Plasterboard	-
Stucanet	-
Wood	-
Stretched ceiling	-

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

LED power supplies

# of Fixtures

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 3

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 3

Dimtype: DALI

Cutout dimension (mm): 45

DELTALIGHT

NIME II 92752

26414 9230 W



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL 3

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL 3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 3

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL 3

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL 3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 3

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 45



300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL 3

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL 3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

DELTALIGHT

NIME II 92752

26414 9230 W



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 3 | 3 | 3

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 6(6) | 6(6) | 6(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 2->4(3) | 4(2) | 3(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 3 | 3

Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 4(3) | 4(2) | 3(1)

Dimtype: DALI

Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 2->9(10) | 9(6) | 7(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 2->4(3) | 3(2) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 4(3) | 3(2) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 5->7 | 4->7 | 4->6 | 3->6

Dimtype: non-dimmable

Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER 2->3 | 3 | 3

Dimtype: non-dimmable

Cutout dimension (mm): 50

DELTALIGHT

NIME II 92752

26414 9230 W



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 — 4 | 4 | 4

Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 — 4 | 4 | 4

Dimtype: DALI

Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL — 6(6) | 5(5) | 5(4)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 4 | 4 | 4

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 — 2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 — 3->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 — 2->2 | 2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 — 3->4 | 3->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 3 | 3 | 2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 — 4(3)

Dimtype: non-dimmable

Cutout dimension (mm): 60

DELTALIGHT

NIME II 92752

26414 9230 W



21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 3(1)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 4(2)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 30



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 30



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 30

Notes: