



ENTERO RD-L TRIMLESS WALLWASH 927


28477 9200 GC

AVAILABLE IN


NOIR 28477 9200 B

COULEUR OR 28477 9200 GC

BLANC 28477 9200 W



Ø115



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
RECESSED DEPTH (MM)	165
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non réglable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,3-16,4W / CRI>90 (R9: 60) / 2700K / 1561-2195lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2195lm // 16,4W // 134lm/W
LED TECHNICS (LUMINAIRE)	1806lm // 18,9W // 96lm/W

Requirements

MOUNTING KIT ENTERO ROUND L

LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : [28477_XXX0_HAND.pdf](#)




ENTERO RD-L TRIMLESS WALLWASH 927

28477 9200 GC

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	 28400 0030 - MOUNTING KIT ENTERO RD-L Required
 Plasterboard	 28400 0030 - MOUNTING KIT ENTERO RD-L Required
 Stucanet	 28400 0030 - MOUNTING KIT ENTERO RD-L Required
 Concrete + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L Required
 Lintel + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L Required
 Hollow-core slab + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L Required
 Stretched ceiling	 28400 0150 - MOUNTING KIT ENTERO RD-L WSC Required
	 28400 0090 - MOUNTING KIT ENTERO RD-L CSC Required

FINISH YOUR SPECIFICATION

les alimentations led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
 300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30		1
 300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45		1
 300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL Dimtype: non dimmable Cutout dimension (mm): 30		1

ENTERO RD-L TRIMLESS WALLWASH 927

28477 9200 GC

	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	1	☐
Dimtype: WDL = dimmable sans fil			
Cutout dimension (mm): 45			
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	1	☐
Dimtype: 1 à 10 V			
Cutout dimension (mm): 30			
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 45			
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	1	☐
Dimtype: non dimmable			
Cutout dimension (mm): 30			
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	1	☐
Dimtype: WDL = dimmable sans fil			
Cutout dimension (mm): 45			
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	1 1	☐
Dimtype: fin de phase ou bouton poussoir			
Cutout dimension (mm): 56			
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	2(2) 2(2)	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir			
Cutout dimension (mm): 82			
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	1(1) 1(0)	☐
Dimtype: 1 à 10 V ou bouton poussoir			
Cutout dimension (mm): 72			
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	1	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir			
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1(1) 1(0)	☐
Dimtype: DALI			
Cutout dimension (mm): 72			

ENTERO RD-L TRIMLESS WALLWASH 927







28477 9200 GC

	<u>300 90 69</u> LED POWER SUPPLY MULTI-POWER HV DIM9	3(3) 3(2)	☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
	Cutout dimension (mm): 84		
	<u>300 90 124</u> LED POWER SUPPLY MULTI-POWER DIM7	1(1) 1(0)	☐
	Dimtype: 1 à 10 V ou bouton poussoir		
	Cutout dimension (mm): 55		
	<u>300 90 125</u> LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1) 1(0)	☐
	Dimtype: DALI		
	Cutout dimension (mm): 55		
	<u>300 90 135</u> LED POWER SUPPLY MULTI-POWER HV	2->2 2	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 90		
	<u>21012 0010</u> LED POWER SUPPLY MULTI POWER	1 1	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 50		
	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1	1 1	☐
	Dimtype: 1 à 10 V		
	Cutout dimension (mm): 54		
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5	1 1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 54		
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL	2(2) 2(2)	☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 84		
	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL	1 1	☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 54		
	<u>21012 0268</u> LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	1	☐
	Dimtype: fin de phase		
	Cutout dimension (mm): 50		

DELTALIGHT

ENTERO RD-L TRIMLESS WALLWASH 927


28477 9200 GC

	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	1 1 ☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	1(1) ☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	1(0) ☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	1 ☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	1 ☐

kit de montage

	28400 0030 MOUNTING KIT ENTERO RD-L Cutout dimension (mm): 162	☐
--	---	--------------------------

kit de montage plafond tendu

	28400 0090 MOUNTING KIT ENTERO RD-L CSC	☐
--	--	--------------------------

ENTERO RD-L TRIMLESS WALLWASH 927

28477 9200 GC



28400 0150 MOUNTING KIT ENTERO RD-L WSC



Notes: