




SOLI - FORM 90 DOWN-UP 92767 MDL

27137 9220 B-FG

AVAILABLE IN
BLACK-BLACK 27137 9220 B-B
BLACK-FLEMISH GOLD 27137 9220 B-FG
WHITE-BLACK 27137 9220 W-B
WHITE-WHITE 27137 9220 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.36 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 10,5W / CRI>90 (R9: 50) / 2700K / 1519lm UP: LED cluster 10,5W / CRI>90 (R9: 50) / 2700K / 1519lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 1519lm // 10,5W // 144lm/W UP: 1519lm // 10,5W // 144lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 1291lm // 12,1W // 107lm/W UP: 1018lm // 12,1W // 84lm/W
Requirements	
LED POWER SUPPLY 48V-DC	
Options	
DIMMABLE MODULATOR	

SOLI - FORM 90 DOWN-UP 92767 MDL

27137 9220 B-FG

For detailed installation instructions, please consult the manual : [27137_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

8

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

8


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

4


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

10

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W


4

Dimtype: non-dimmable

Cutout dimension (mm): 40

SOLI - FORM 90 DOWN-UP 92767 MDL

27137 9220 B-FG



21012 0240 LED POWER SUPPLY 48V-DC / 200W

Dimtype: non-dimmable

Cutout dimension (mm): 40

8 ☐

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
  27111 0020 SOLI - PROFILE 2m	
  27111 0030 SOLI - PROFILE 3m	

Notes: