



M52 - SPY 391 L 92720 MDL

REFERENCE

24440 9220 FG

AVAILABLE IN



BLACK 24440 9220 B

FLEMISH BRONZE 24440 9220 FBR

FLEMISH GOLD 24440 9220 FG

GOLD COLOURED 24440 9220 GC

WHITE 24440 9220 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCLED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	652lm // 9,9W // 66lm/W

Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

Requirements

SPY 39 L TUBE

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [24440_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

Dimtype: WDL = wireless dimmable


19

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

Dimtype: 1-10V or DALI or push button

19



300 90 012 SMART 48 MODULATOR WD

Dimtype: WDL = wireless dimmable


19

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN


Dimtype: non-dimmable

10

DELTALIGHT

M52 - SPY 391 L 92720 MDL

24440 9220 FG




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

☐

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

☐

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W


20

☐

Dimtype: non-dimmable

Cutout dimension (mm): 40

Finish your product



24144 0020 B SPY 39 L TUBE B

☐

24144 0020 FBR SPY 39 L TUBE FBR

☐

24144 0020 FG SPY 39 L TUBE FG

☐

24144 0020 GC SPY 39 L TUBE GC

☐


24144 0020 W SPY 39 L TUBE W

☐


COMPATIBLE COMPOSABLES

SPLITLINE M52 profile

Available Colours



420 52 10 00 SPM52 - PROFILE 1m





420 52 20 00 SPM52 - PROFILE 2m



DELTALIGHT

M52 - SPY 391 L 92720 MDL

24440 9220 FG

	420 52 30 00 SPM52 - PROFILE 3m	
	24413 0000 SPM52 - PROFILE	

Notes: