
DELTALIGHT




MINI DEEP RINGO II OK 93037

REFERENCE 19425 9330 BROB

AVAILABLE IN
NOIR 19425 9330 B
ALU BROSSÉ 19425 9330 BRA
ANTHRACITE BROSSÉ 19425 9330 BRAT
BRONZE BRUN BROSSÉ 19425 9330 BRBB
CUIVRE BROSSÉ 19425 9330 BRCU
OR BROSSÉ 19425 9330 BRG
BRONZE VIEUX BROSSÉ 19425 9330 BROB
CRÈME 19425 9330 CR
FLEMISH BRONZE 19425 9330 FBR
FLEMISH GOLD 19425 9330 FG
BLANC 19425 9330 W





View on website

General info	
LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 71
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° à 30° inclinable, 360° rotatif
INFORMATION	REFLECTOR WFL-37° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm
RVALUES	Rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	37°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	724lm // 10W // 73lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

MINI DEEP RINGO II OK 93037

19425 9330 BROB


For detailed installation instructions, please consult the manual : **19425_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **System ceiling**	-
 **Plasterboard**	-
 **Stucanet**	-
 **Wood**	-
 **Concrete**	-
 **Concrete + plaster**	-
 **Lintel + plaster**	-
 **Hollow-core slab**	-
 **Hollow-core slab + plaster**	-
 **Stretched ceiling**	-

FINISH YOUR SPECIFICATION

les batteries de secours



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

DELTALIGHT


MINI DEEP RINGO II OK 93037

19425 9330 BROB

les alimentations led		# of Fixtures
web2print_power_supply_info_box		Min current | Max current
	**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 **Dimtype: 1 à 10 V** **Cutout dimension (mm): 30**	2
	**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 **Dimtype: DALI** **Cutout dimension (mm): 45**	2
	**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL **Dimtype: non dimmable** **Cutout dimension (mm): 30**	2
	**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL **Dimtype: WDL = dimmable sans fil** **Cutout dimension (mm): 45**	2
	**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 **Dimtype: 1 à 10 V** **Cutout dimension (mm): 30**	2
	**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 **Dimtype: DALI** **Cutout dimension (mm): 45**	2
	**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL **Dimtype: non dimmable** **Cutout dimension (mm): 30**	2
	**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL **Dimtype: WDL = dimmable sans fil** **Cutout dimension (mm): 45**	2
	**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6 **Dimtype: fin de phase ou bouton poussoir** **Cutout dimension (mm): 56**	2 | 2

MINI DEEP RINGO II OK 93037


19425 9330 BROB



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 4(4) | 4(4)

Dimtype: 1 à 10 V ou DALI ou boutton poussoir


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 3(2) | 2(1)


Dimtype: 1 à 10 V ou bouton poussoir

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 2 | -


Dimtype: 1 à 10 V ou DALI ou boutton poussoir



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 2(2) | 2(1)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 2->6(6) | 6(4)

Dimtype: 1 à 10 V ou DALI ou boutton poussoir


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 2(2) | 2(1)

Dimtype: 1 à 10 V ou bouton poussoir


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 2(2) | 2(1)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 3->4 | 2->4

Dimtype: non dimmable


Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER 2 | 2

Dimtype: non dimmable

Cutout dimension (mm): 50




21012 0021 LED POWER SUPPLY MULTI POWER DIM1 3 | 3

Dimtype: 1 à 10 V

Cutout dimension (mm): 54

MINI DEEP RINGO II OK 93037


19425 9330 BROB



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 3 | 3

Dimtype: DALI


Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 4(4) | 4(3)

Dimtype: WDL = dimmable sans fil


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 3 | 3

Dimtype: WDL = dimmable sans fil


Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 1

Dimtype: fin de phase


Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 2->2

Dimtype: fin de phase


Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 1

Dimtype: fin de phase


Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 2->3

Dimtype: fin de phase


Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 2 | 2

Dimtype: fin de phase


Cutout dimension (mm): 48



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 1

Dimtype: fin de phase

Cutout dimension (mm): 40



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 1


Dimtype: fin de phase

Cutout dimension (mm): 40

DELTALIGHT

MINI DEEP RINGO II OK 93037


19425 9330 BROB



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 2(2)

Dimtype: non dimmable


Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 2(1)

Dimtype: non dimmable


Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 2

Dimtype: DALI

Cutout dimension (mm): 30



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 2

Dimtype: DALI

Cutout dimension (mm): 30

Notes: