



MINIGRID IN 2 HI LED



100034 0000 B-B

AVAILABLE IN

BLACK-BLACK 100034 0000 B-B

WHITE-BLACK 100034 0000 W-B

WHITE-WHITE 100034 0000 W-W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 214 x 111
RECESSED DEPTH (MM)	70
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
Electrical info	
	2 x QPAR51 max.10W
CLASS	II
DIM TYPE	mains (phase cut-off)
Lightsource info	
LIGHTSOURCE NAME	GU10
Remarks	
lamp not included	

For detailed installation instructions, please consult the manual : [100034_0000_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
System ceiling	-
Plasterboard	-

DELTALIGHT


MINIGRID IN 2 HI LED

100034 0000 B-B

	Stucanet	 202 72 99 02 - PLASTERKIT 127	Required
	Wood	-	
	Concrete + plaster	 202 72 99 02 - PLASTERKIT 127	Required
	Lintel + plaster	 202 72 99 02 - PLASTERKIT 127	Required
	Hollow-core slab + plaster	 202 72 99 02 - PLASTERKIT 127	Required
	Stretched ceiling	-	

FINISH YOUR SPECIFICATION

Plasterkits

	202 72 99 02 PLASTERKIT 127	
Cutout dimension (mm): 120 x 225		

Notes: