
DELTALIGHT




NOCTA SQ155 DOWN-UP SP 930 DIM5

REFERENCE 30131 9305 N

AVAILABLE IN
ALU GREY 30131 9305 A
BLACK 30131 9305 B
FLEMISH BRONZE OUTDOOR 30131 9305 FBRX
ANTHRACITE 30131 9305 N
WHITE 30131 9305 W





View on website

General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.8 x LENS INCL.DIMMABLE LED POWER SUPPLY 700 mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	8 x (LED array 2W / CRI>90 (R9: 60) / 3000K / 240lm)
TM-30 VALUES	Rf: 91 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	1920lm // 16W // 120lm/W
LED TECHNICS (LUMINAIRE)	1493lm // 18,4W // 81lm/W

For detailed installation instructions, please consult the manual : **30131_XXX5_HAND.pdf**

DELTALIGHT

NOCTA SQ155 DOWN-UP SP 930 DIM5

30131 9305 N

Notes: