





SPY 27 CLIP 93030

24118 9320 B-B

AVAILABLE IN
NOIR-NOIR 24118 9320 B-B
FLEMISH BRONZE-NOIR 24118 9320 FBR-B
FLEMISH GOLD-NOIR 24118 9320 FG-B
ENTIÈREMENT BLANC 24118 9320 FW
COULEUR OR-NOIR 24118 9320 GC-B
BLANC-BLANC 24118 9320 W-W











[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Semi-encasté
CUTOUT SHAPE/SIZE (MM)	circulaire - 43
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° à 85° inclinable, 355° rotatif
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 350mA-DC SPY 27 TUBE included (B for all versions W for FW version)
Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, LCA
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	480lm // 6,7W // 72lm/W
Requirements	
LED POWER SUPPLY 350mA-DC DIM	
Accessories	
VISOR 27	

For detailed installation instructions, please consult the manual : [24118_XXX0_HAND.pdf](#)











FINISH YOUR SPECIFICATION

les alimentations led			# of Fixtures
 web2print_power_supply_info_box			Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2	☐
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	2	☐
	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL Dimtype: non dimmable Cutout dimension (mm): 30	2	☐
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45	2	☐
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: fin de phase ou bouton poussoir Cutout dimension (mm): 56	2	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 82	4(4)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 72	2(2)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir	2	☐

DELTALIGHT

SPY 27 CLIP 93030






24118 9320 B-B

	<u>300 90 68</u> LED POWER SUPPLY MULTI-POWER DIM5	2(2) ☐
Dimtype: DALI		
Cutout dimension (mm): 72		
	<u>300 90 69</u> LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) ☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
Cutout dimension (mm): 84		
	<u>300 90 124</u> LED POWER SUPPLY MULTI-POWER DIM7	3(2) ☐
Dimtype: 1 à 10 V ou bouton poussoir		
Cutout dimension (mm): 55		
	<u>300 90 125</u> LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2) ☐
Dimtype: DALI		
Cutout dimension (mm): 55		
	<u>300 90 135</u> LED POWER SUPPLY MULTI-POWER HV	3->4 ☐
Dimtype: non dimmable		
Cutout dimension (mm): 90		
	<u>21012 0010</u> LED POWER SUPPLY MULTI POWER	2 ☐
Dimtype: non dimmable		
Cutout dimension (mm): 50		
	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1	3 ☐
Dimtype: 1 à 10 V		
Cutout dimension (mm): 54		
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5	3 ☐
Dimtype: DALI		
Cutout dimension (mm): 54		
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL	4(4) ☐
Dimtype: WDL = dimmable sans fil		
Cutout dimension (mm): 84		
	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL	3 ☐
Dimtype: WDL = dimmable sans fil		
Cutout dimension (mm): 54		

DELTALIGHT

SPY 27 CLIP 93030



24118 9320 B-B

	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	2 ☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1 ☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(2) ☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2 ☐

modifier les dispositifs de lumière

	24144 0040 B VISOR 27 B	☐
--	--------------------------------	--------------------------


COMPATIBLE COMPOSABLES

ZOOVER 4CLIP	Available Colours
	28215 0005 ZOOVER 4CLIP 120 LIGHT GREY DIM5
	28216 0005 ZOOVER 4CLIP 120 DARK GREY DIM5


DELTALIGHT

SPY 27 CLIP 93030

24118 9320 B-B



28217 0005 ZOOVER 4CLIP 140 LIGHT GREY DIMS



28218 0005 ZOOVER 4CLIP 140 DARK GREY DIMS



Notes: