DELTALIGHT

NOCTA SQ155 DOWN-UP WFL 927

REFERENCE 30132 9200 N

AVAILABLE IN
ALU GREY 30132 9200 A
BLACK 30132 9200 B
FLEMISH BRONZE OUTDOOR 30132 9200 FBRX
ANTHRACITE 30132 9200 N
WHITE 30132 9200 W





View on website

General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.8 x LENS INCL.LED POWER SUPPLY 700 mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	8 x (LED array 2W / CRI>90 (R9: 55) / 2700K / 220lm)
TM-30 VALUES	Rf: 91 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	1760lm // 16W // 110lm/W
LED TECHNICS (LUMINAIRE)	1258lm // 18,4W // 68lm/W

For detailed installation instructions, please consult the manual : **30132_XXX0_HAND.pdf**

DELTALIGHT

NOCTA SQ155 DOWN-UP WFL 927

30132 9200 N

Notes: