
DELTALIGHT




OCTAV 39 ON 1 92740 DIM8

REFERENCE 29018 9238 B-B

AVAILABLE IN
BLACK-BLACK 29018 9238 B-B
WHITE-WHITE 29018 9238 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	705lm // 9,9W // 71lm/W

Requirements

SPY 39 L TUBE

For detailed installation instructions, please consult the manual : **29018_XXX8_HAND.pdf**


DELTALIGHT

OCTAV 39 ON 1 92740 DIM8

29018 9238 B-B

FINISH YOUR SPECIFICATION

Finish your product

	**24144 0020 B**	SPY 39 L TUBE B	☐
	24144 0020 FBR	SPY 39 L TUBE FBR	☐
	24144 0020 FG	SPY 39 L TUBE FG	☐
	24144 0020 GC	SPY 39 L TUBE GC	☐
	24144 0020 W	SPY 39 L TUBE W	☐

Notes: