





INFORM 40 SQ 180 DOWN 94063 DIM5

30713 9435 W-B

AVAILABLE IN

BLACK-BLACK 30713 9435 B-B

WHITE-BLACK 30713 9435 W-B



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver EXCL.CABLE SUSPENSION

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	HO: LED cluster 27W / CRI>90 (R9: 50) / 4000K / 3987lm Or LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 VALUES	Rf: 90 / Rg: 101 rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	HO: 3987lm // 27W // 148lm/W Or 2643lm // 16,3W // 162lm/W
LED TECHNICS (LUMINAIRE)	HO: 2759lm // 31W // 89lm/W Or 1829lm // 18,7W // 98lm/W

Options

INF40 SQ 160/180 - SUSPENSION SET
CABLE BASE R / S

DELTALIGHT

INFORM 40 SQ 180 DOWN 94063 DIM5

30713 9435 W-B

For detailed installation instructions, please consult the manual : [30713_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	<u>203 99 55 ANO</u> CABLE BASE R ANO	☐
	<u>203 99 55 B</u> CABLE BASE R B	☐
	<u>203 99 55 W</u> CABLE BASE R W	☐
	<u>203 99 56 ANO</u> CABLE BASE S ANO	☐
	<u>203 99 56 B</u> CABLE BASE S B	☐
	<u>203 99 56 W</u> CABLE BASE S W	☐

Fixation components

	<u>30710 0010 B</u> INF40 SQ 160/180 - SUSPENSION SET 1,6m B	☐
	<u>30710 0010 W</u> INF40 SQ 160/180 - SUSPENSION SET 1,6m W	☐
	<u>30710 0030 B</u> INF40 SQ 160/180 - SUSPENSION SET 3,0m B	☐
	<u>30710 0030 W</u> INF40 SQ 160/180 - SUSPENSION SET 3,0m W	☐

DELTALIGHT

INFORM 40 SQ 180 DOWN 94063 DIM5

30713 9435 W-B

Notes: