



## OML50 C - LED ARRAY UP HO 2624mm 930 DIM5

31135 9305

 [Bekijk op website](#)



Algemene info	
<b>LOCATIE</b>	binnen
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	1
<b>INFO</b>	CLUSTER UP: 2663lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Elektrische info	
<b>ELEKTRISCH</b>	220-240V / 0 50-60Hz
<b>KLASSE</b>	I
<b>VOEDING INBEGREPEN</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGIE KLASSE</b>	E
<b>CERTIFICATES</b>	EPD, RCM
Info lichtbron	
<b>LIGHTSOURCE NAME</b>	LED
<b>LICHTBRON</b>	LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm
<b>TM-30 WAARDEN</b>	Rf: 92 / Rg: 100
<b>SMDC</b>	SDCM3
<b>RISK-GROEP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNIEK (LICHTBRON)</b>	6989lm // 48,4W // 145lm/W

### Opties

WIRELESS CONTROL DIM5

Notes: